


Overview

HP Z840 Workstation



- | | | | |
|----|----------------------------|----|--|
| 1. | Slimline Optical Drive Bay | 4. | HDD Activity LED |
| 2. | 2 External 5.25" Bays | 5. | Front I/O: 4 USB 3.0 (Top Port has Charging Capability), 1 Headset, 1 Microphone |
| 3. | Power Button | | |

Overview



6. Choice of 850W, 88% or 1125W, 90% Efficient Power Supplies

7. 16 DIMM Slots for DDR4 ECC Memory

8. 2 External 5.25" Bays

9. 4 Internal 3.5" Bays

10. Rear I/O:

Rear Power Button

4 USB 3.0

2 USB 2.0

1 Serial

PS/2 keyboard and mouse

2 RJ-45 to integrated Gigabit LAN

1 Audio Line-In (can be retasked as microphone)

1 Audio Line-Out

11. 2 Intel Xeon Processors E5-2600 v3 family

12.

- Slot 1: PCIe Gen3 x4
- Slot 2: PCIe Gen3 x16
- Slot 3: PCIe Gen3 x8 - Available ONLY when 2nd processor is installed
- Slot 4: PCIe Gen3 x16 - Available ONLY when 2nd processor is installed
- Slot 5: PCIe Gen2 x4 when 1 CPU is installed. Transforms to PCIe Gen3 x8 when 2nd CPU is installed
- Slot 6: PCIe Gen3 x16
- Slot 7: PCIe Gen2 x1

13. 6 SATA, 8 SAS Ports

14. 2 USB 2.0 Ports, 1 USB 3.0 Port

Overview

Overview

Form Factor Operating Systems

Rackable Tower

Preinstalled:

- Windows 7 Professional 64-bit
- Windows 8.1 Pro 64-bit downgrade to Windows 7 Professional 64-bit**
- Windows 8.1 Pro 64-bit OS
- Windows 8.1 Emerging Market
- Ubuntu 14.04
- HP Installer Kit for Linux (includes drivers for 64-bit OS versions of RHEL 6 & 7, SUSE Linux Enterprise Desktop 11 and Ubuntu 14.04)
- Red Hat Enterprise Linux (RHEL) Workstation (Paper license with 1 year support; no preinstalled OS)

Supported:

- Windows 7 Enterprise 64-bit
- Windows 8/8.1 Enterprise 64-bit

NOTES: For detailed OS/hardware support information for Linux, see:
http://www.hp.com/support/linux_hardware_matrix

Available Processors

Name	Clock Speed (GHz)	Cores	Cache (MB)	Memory Speed (MHz)	QPI Speed (GT/s)	Hyper Threading	Featuring Intel® vPro™ Technology	Intel® Turbo Boost Technology ¹	TDP (W)
INTEL® XEON® E5-2699 v3 processor	2.3	18	45	2133	9.6	YES	YES	5/13	145
INTEL® XEON® E5-2697 v3 processor	2.6	14	35	2133	9.6	YES	YES	5/10	145
INTEL® XEON® E5-2695 v3 processor	2.3	14	35	2133	9.6	YES	YES	5/10	120
INTEL® XEON® E5-2687W v3 processor	3.1	10	25	2133	9.6	YES	YES	1/4	160
INTEL® XEON® E5-2690 v3 processor	2.6	12	30	2133	9.6	YES	YES	5/9	135
INTEL® XEON® E5-2667 v3 processor	3.2	8	20	2133	9.6	YES	YES	2/4	135
INTEL® XEON® E5-2683 v3 processor	2.0	14	35	2133	9.6	YES	YES	5/10	120
INTEL® XEON® E5-2680 v3 processor	2.5	12	30	2133	9.6	YES	YES	4/8	120
INTEL® XEON® E5-2670 v3 processor	2.3	12	30	2133	9.6	YES	YES	3/8	120
INTEL® XEON® E5-2643 v3 processor	3.4	6	20	2133	9.6	YES	YES	2/3	135
INTEL® XEON® E5-2660 v3 processor	2.6	10	25	2133	9.6	YES	YES	3/7	105
INTEL® XEON® E5-2650 v3 processor	2.3	10	25	2133	9.6	YES	YES	3/7	105
INTEL® XEON® E5-2637 v3 processor	3.5	4	15	2133	9.6	YES	YES	1/2	135

Overview

processor									
INTEL® XEON® E5-2640 v3 processor	2.6	8	20	1866	8.0	YES	YES	2/8	90
INTEL® XEON® E5-2630 v3 processor	2.4	8	20	1866	8.0	YES	YES	2/8	85
INTEL® XEON® E5-2623 v3 processor	3.0	4	10	1866	8.0	YES	YES	3/5	105
INTEL® XEON® E5-2620 v3 processor	2.4	6	15	1866	8.0	YES	YES	2/8	85
INTEL® XEON® E5-2609 v3 processor	1.9	6	15	1600	6.4	NO	YES	N/A	85
INTEL® XEON® E5-2603 v3 processor	1.6	6	15	1600	6.4	NO	YES	N/A	85
¹ The specifications shown in this column represent the following: (all core maximum turbo steps, one core maximum turbo steps). Turbo boost stepping occurs in 100MHz increments. Processors that do not have turbo functionality are denoted as N/A. E5-2687Wv3, E5-2690v3, E5-2695v3, E5-2697v3 and E5-2699v3 REQUIRE the 1125W (1450W at 200V Input Voltage) Power Supply Option.									

Disclaimers

When ordering two processors, the second processor must be the same as the first. Intel processor numbers are not a measurement of higher performance. Processor numbers differentiate features within each processor family, not across different processor families. See: http://www.intel.com/products/processor_number/ for details.

Quad-Core, Six-Core, Eight-Core, 10-Core, 12-Core, 14-Core, 16-Core and 18-Core technologies are designed to improve performance of multithreaded software products and hardware-aware multitasking operating systems and may require appropriate operating system software for full benefits; check with software provider to determine suitability; Not all customers or software applications will necessarily benefit from use of these technologies.

64-bit computing on Intel® 64 architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers, and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel® 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. See: <http://www.intel.com/info/em64t> for more information.

Intel® Xeon® processors E5-2637v3, E5-2643v3, E5-2670v3, E5-2680v3, E5-2683v3, E5-2667v3, E5-2687Wv3, E5-2690v3, E5-2695v3, E5-2697v3 and E5-2699v3 REQUIRE the 1125W (1450W at 200V Input Voltage) Power Supply Option.

Form Factor

Tower

Color

Black /Hematite

I/O Slots (see system board section for more details)

Slot 1: PCIe Gen3 x4
 Slot 2: PCIe Gen3 x16
 Slot 3: Gen3 x8 - Available ONLY when 2nd processor is installed
 Slot 4: Gen3 x16 - Available ONLY when 2nd processor is installed
 Slot 5: PCIe Gen2 x4 when 1 CPU is installed. Transforms to PCIe Gen3 x8 when 2nd CPU is installed
 Slot 6: PCIe Gen3 x16
 Slot 7: PCIe Gen 2x1

The PCIe x8 connectors are open ended, allowing a PCIe x16 card to be seated in the slot.

Bays (see storage section) Total Bays = 7

Overview

for more details)

4 Internal 3.5" storage bays
2 External 5.25" bays
1 External Slim-line Optical bay

Internal Bays

4 internal 3.5" bays (All 4 include acoustic dampening rail assemblies)

External Bays

2 external 5.25" bays

- Top bay device depth limit: 206mm
- Bottom bay device depth limit: 206mm

Front I/O

- 4 USB 3.0
- 1 Combo Headset
- 1 Microphone

Rear I/O

- 4 USB 3.0
- 2 USB 2.0
- 1 Serial
- PS/2 keyboard and mouse
- 2 RJ-45 to integrated Gigabit LAN
- 1 Audio Line-In (can be retasked as microphone)
- 1 Audio Line-Out

Internal USB

- 2 USB 2.0 ports available with a single 2x5 header.
- 1 USB 3.0 port available with a shrouded 20-pin connector.

The 2x5 header can be converted to a standard (Type-A) USB connector through the use one HP Internal USB Port Kit (EM165AA). This port kit uses one half of the 2x5 header.

Chassis Dimensions (H x W x D)

Footprint Dimensions:

H: 17.5" [444.5mm]
W: 8.0" [203.2mm]
D: 20.7" [525.8mm] (measured to the rear of service panel)

Maximum Dimensions:

H: 17.5" [444.5mm]
W: 8.0" [203.2mm]
D: 20.9" [530.9mm] (measured to the embossment for the rear chassis fans)

Rack Dimensions: 5U

System Weight

Exact weights depend upon configuration.

- Minimum config: 21.1kg (46.7lbs.)
- Typical config: 22.8kg (50.4lbs.)
- Maximum config: 29.2kg (64.3lbs.)

Temperature

Operating: 5° to 35°C (40° to 95°F)
Non-operating: -40° to 70°C (-40° to 158°F)

Humidity

Operating: 8% to 85%
Non-operating: 8% to 90%

Operating: 3,000 m; 10,000 feet

Overview

Non-operating: 9,100 m; 30,000 feet

Maximum Altitude (non-pressurized) Operating: 3,048m (10,000feet)
Non-operating: 9,100m (30,000feet)

Power Supply Choice of:

- 850W 88% Efficient wide-ranging, active Power Factor Correction
- 1125W 90% Efficient wide-ranging, active Power Factor Correction

NOTE: The 1125W (1450W at 200V Input Voltage) power supply can also supply 1275W of output power when the input voltage is greater than 105V. If the input voltage is less than 105V, but greater than 90V for any reason, the maximum power that can be drawn is 1125W. An uninterruptible power supply (UPS) is highly recommended if 1275W output power is desired. The 1125W Power Supply can also supply 1450W of output power when the input voltage is greater than 200V under all conditions.

The Z820 power supply efficiency reports can be found at these links:

850W - http://www.plugloadsolutions.com/psu_reports/HEWLETT%20PACKARD_719798-001_850W_ECOS%203882_Report.pdf

1125W - http://www.plugloadsolutions.com/psu_reports/HEWLETT%20PACKARD_719799-001_1125W_ECOS%203883_Report.pdf

Interfaces Supported

- 6 channel SATA 6.0 Gb/s interface
- 8-channel 6 Gb SAS interface
 - 8 SAS connectors on the motherboard, SAS ports can be ported externally by using the SAS Bulkhead and/or Back Panel connector Kits
- Factory integrated RAID available for SATA/SAS drives (RAID 0, 0 Data, 1, 5, and 10)
- USB 3.0, USB 2.0

Hard Drive Controller Supported Workstation ISV Certifications

SATA and SAS controllers

See the latest list of certifications at <http://www.hp.com/united-states/campaigns/workstations/partnerships.html>

Supported Components

Processors*

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Z840 Intel Xeon E5-2600 v3 Series CPU				
Xeon E5-2603 v3 1.6 1600 6C CPU	Y	Y	J9V77AA	
Xeon E5-2609 v3 1.9 1600 6C CPU	Y	Y	J9V76AA	
Xeon E5-2620 v3 2.4 1866 6C CPU	Y	Y	J9V75AA	
Xeon E5-2623 v3 3.0 1866 4C CPU	Y	Y	J9Q18AA	
Xeon E5-2630 v3 2.4 1866 8C CPU	Y	Y	J9Q17AA	
Xeon E5-2637 v3 3.5 2133 4C CPU	Y	Y	J9Q15AA	
Xeon E5-2640 v3 2.6 1866 8C CPU	Y	Y	J9Q16AA	
Xeon E5-2643 v3 3.4 2133 6C CPU	Y	Y	J9Q12AA	
Xeon E5-2650 v3 2.3 2133 10C CPU	Y	Y	J9Q14AA	
Xeon E5-2660 v3 2.6 2133 10C CPU	Y	Y	J9Q13AA	
Xeon E5-2667 v3 3.2 2133 8C CPU	Y	Y	J9Q08AA	
Xeon E5-2670 v3 2.3 2133 12C CPU	Y	Y	J9Q11AA	
Xeon E5-2680 v3 2.5 2133 12C CPU	Y	Y	J9Q10AA	
Xeon E5-2683 v3 2.0 2133 14C CPU	Y	Y	J9Q09AA	
Xeon E5-2687Wv3 3.1 2133 10C CPU	Y	Y	J9Q06AA	
Xeon E5-2690 v3 2.6 2133 12C CPU	Y	Y	J9Q07AA	
Xeon E5-2695 v3 2.3 2133 14C CPU	Y	Y	J9Q05AA	
Xeon E5-2697 v3 2.6 2133 14C CPU	Y	Y	J9Q04AA	
Xeon E5-2699 v3 2.3 2133 18C CPU	Y	Y	J9Q03AA	

Intel® Xeon® processors E5-2637v3, E5-2643v3, E5-2670v3, E5-2680v3, E5-2683v3, E5-2667v3, E5-2687Wv3, E5-2690v3, E5-2695v3, E5-2697v3 and E5-2699v3 REQUIRE the 1125W Power Supply Option.

When ordering two processors, the second processor must be the same as the first. Intel processor numbers are not a measurement of higher performance. Processor numbers differentiate features within each processor family, not across different processor families.

Monitors / Displays

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Z Display Z22i 21.5-inch IPS LED Backlit Monitor			D7Q14A8	
HP Z Display Z23i 23-inch IPS LED Backlit Monitor			D7Q13A8	
HP Z Display Z24i 24-inch IPS LED Backlit Monitor			D7P53A8	
HP Z Display Z27i 27-inch IPS LED Backlit Monitor			D7P92A8	
HP Z Display Z30i 30-inch IPS LED Backlit Monitor			D7P94A8	
HP DreamColor LP2480zx Professional Display			GV546A8	
HP DreamColor Z24x Professional Display			E9Q82A8	
HP DreamColor Z27x Professional Display			D7R00A8	

Supported Components

Storage / Hard Drives

**Sub-Section
Description/Notes**

NOTES: NCQ (Native Command Queuing) not supported in Red Hat Enterprise Linux
For hard drives, 1 GB = 1 billion bytes; TB = 1 trillion bytes. Actual formatted capacity is less. Up to 12 GB of hard drive (or system disk) is reserved for the system recovery software (XP and XP Pro). Up to 3 GB of system disk is reserved for system recovery software (Vista).

SAS Hard Drives	SAS Hard Drives for HP Workstations	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
	600GB* SAS 15K rpm 6Gb/s 3.5" HDD	Y	Y	VM647AA	
	300GB* SAS 15K rpm 6Gb/s 3.5" HDD	Y	Y	LU967AA	
	HP 300GB SAS 10K SFF HDD	Y	Y	A2Z20AA	
	HP 600GB SAS 10K SFF HDD	Y	Y	A2Z21AA	
	HP 1.2TB* SAS 10K SFF HDD	Y	Y	E2P04AA	
	HP 600GB* SAS 10K SFF HDD	Y	Y	A2Z21AA	
	HP 300GB* SAS 10K SFF HDD	Y	Y	A2Z20AA	
	Up to 5 3.5" SATA drives supported				
	Up to 5 3.5" SAS drives supported				
	Up to 8 2.5" (SFF) SAS drives with the High Density Storage Option or				
	Up to 8 2.5" (SFF) SATA 2.5" drives with the High Density Storage Option				
	8 port SAS Controller included on the system board				

SATA Hard Drives	SATA Hard Drives for HP Workstations	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
	4TB SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	K4T76AA	
	3.0TB* SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	QF298AA	
	2.0TB* SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	QB576AA	
	1TB* SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	LQ037AA	
	500GB* SATA 7200 rpm 6Gb/s 3.5" HDD	Y	Y	LQ036AA	
	500GB* SATA 7.2K SED SFF HDD	Y	N	(not available today as After Market Option)	
	Up to 5 3.5" SATA drives supported				
	Up to 5 3.5" SAS drives supported				
	Up to 8 2.5" (SFF) SAS drives with the High Density Storage Option or				
	Up to 8 2.5" (SFF) SATA 2.5" drives with the High Density Storage Option				

SATA Solid State Drives	SATA SSDs for HP Workstations	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
	HP 128GB* SATA 6Gb/s SSD	Y	Y	A3D25AA	
	HP 256GB* SATA 6Gb/s SSD	Y	Y	A3D26AA	
	HP 512GB* SATA 6Gb/s SSD	Y	Y	D8F30AA	
	HP 1TB* SATA 6Gb/s SSD	Y	Y	F3C96AA	
	Samsung Enterprise 240GB* SATA SSD	Y	Y	F0W94AA	
	Samsung Enterprise 480GB* SATA SSD	Y	Y	F0W95AA	
	Intel Pro 1500 180GB* SATA SSD	Y	Y	F5Z70AA	

Supported Components

HP 256GB* SATA 6Gb/s SED Opal 1 SSD	Y	Y	G7U67AA	Note 1
-------------------------------------	---	---	---------	--------

Up to 8 SATA SSD drives supported with the High Density Storage Option

NOTE 1:

The 256GB Self-Encrypting Drive (SED) version has similar performance to the standard 256GB SSD. It is also available in Opal 1.0 and Opal 2.0 versions

PCIe Solid State Drives

PCIe SSDs for HP Workstations

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Z Turbo Drive 512GB* SSD	Y	Y	G3G89AA	
HP Z Turbo Drive 256GB* SSD	Y	Y	G3G88AA	

*For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30GB of system disk is reserved for system recovery software.

HP 4-Bay SAS-SATA 2.5in High Density Storage Kit

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP 4-Bay SAS-SATA 2.5in High Density Storage Kit		Y	K5J28AA	

This kit converts two of the native 3.5" HDD bays to enable four SFF (2.5") HDDs or SSDs. Once the kit is installed, it enables independent, tool-free access for these SFF drives. Enterprise class SAS HDDs (15mm) are also supported. Up to two modules are supported in the Z840, which enables up to 8 SFF drives to be added to the internal section of the Z840. HDDs and SSDs are supported with up to 6Gb/s bandwidth.

Notes:

For a video installation guide, please see www.hp.com/go/sml
The installation guide can also be accessed in the Maintenance and Service Guide for your workstation at www.hp.com/support/workstation_manuals

HDD Carrier

HP 4-in-1 SFF (2.5 in) HDD Carrier

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP 4-in-1 SFF (2.5 in) HDD Carrier*		Y	B8K60AA	

* For the Z440, Z640, and Z840, the carrier can be installed in any of the 5.25" ODD bays.

Notes:

Additional controllers may be required to support the additional drives located in this carrier. This kit includes an additional 4 carriers which can be mounted to drives for easy external access and transfer of data between systems.

Hard Drive Controllers

Factory integrated RAID on motherboard for SATA drives

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
RAID 0 Configuration – Striped Array	Y	N		Note 1
RAID 0 Data Configuration -- Boot/OS Drive + 2 Drive Striped Array	Y	N		Note 2
RAID 1 Configuration – Mirrored Array	Y	N		Note 3
RAID 10 Configuration - Striped/Mirrored Array	Y	N		

Supported Components

RAID 5 Configuration - Parity Array	Y	N		Note 4
HP SAS Back Panel Connector kit	Y	Y		
<i>Must have 4 or fewer SAS hard drives to configure this option</i>				
HP SAS Back Panel Bulkhead Connector Kit	Y	Y		
<i>HP SAS Back Panel Connector kit required. Internal SAS HD drives are not supported</i>				
LSI iBBU09 Battery Backup Unit	Y	Y	E0X19AA	
LSI 9270-8i SAS 6Gb/s ROC RAID Card	Y	Y	E0X21AA	
Integrated LSI SAS 2308 Controller with RAID 0/1/1E/10	Y	N		
Integrated SATA 6.0 Gb/s Controller	Y	N		

NOTE 1: Minimum of 2 hard drives needed. All hard drives must be identical (size/speed/type/bus/functional capabilities). Must have 2, 3 or 4 HD Drives.

NOTE 2: Minimum of 3 SATA hard drives needed. All hard drives must be identical (size/speed/type/bus/functional capabilities).

At least 3 HD Drives required. May have 4th and 5th HD Drives. Drives must be the same drive (size/speed/type/functional capability).

NOTE 3: 2 SATA or 2 SAS hard drives required. All hard drives must be identical (size/speed/type/bus/functional capabilities).

NOTE 4: Minimum of 3 SATA hard drives needed. All SATA hard drives must be identical (size/speed/type/bus/functional capabilities). Must have 3 or 4 HD Drives. 5 HD Drives not allowed.

NOTE: SATA hardware RAID is supported on Linux systems that have support for the Intel RSTe technology. The Linux kernel, with built-in software RAID, provides excellent functionality and performance. It is a good alternative to hardware-based RAID. Please visit http://www.hp.com/support/linux_hardware_matrix for RAID capabilities with Linux.

LSI RAID Definitions:

IS: Striping of 2 or more HDDs into a single logical volume

IM: Mirroring of 2 HDDs into a single logical volume

IME: Mirroring of 3 or more HDDs into a single logical volume

NOTE: Specific user-configured hardware SAS RAID configurations are supported on this Linux system. Please visit: http://www.hp.com/support/linux_hardware_matrix for details

Graphics

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes	Supported # of cards	Mixed?
Professional 2D						
NVIDIA NVS 310 512MB Graphics	Y	Y	A7U59AA	Note 1	4	
NVIDIA NVS 315 1GB Graphics (for HP Workstations)	Y	Y	E1U66AA	Note 1	4	
NVIDIA NVS 510 2GB Graphics	N	Y	C2J98AA	Note 2	2	
Entry 3D						
NVIDIA Quadro K420 1GB Graphics	Y	Y	J3G86AA		2	
NVIDIA Quadro K620 2GB Graphics	Y	Y	J3G87AA		2	
AMD FirePro W2100 2GB Graphics	Y	Y	J3G91AA		2	

Supported Components

Mid-range 3D

AMD FirePro W5100 4GB Graphics	Y	Y	J3G92AA	2
NVIDIA Quadro K2200 4GB Graphics	Y	Y	J3G88AA	2

High End 3D

NVIDIA Quadro K4200 4GB Graphics	Y	Y	J3G89AA	2
NVIDIA Quadro K5200 8GB Graphics	Y	Y	J3G90AA	2
NVIDIA Quadro K6000 12GB Graphics	Y	Y	C2J96AA	2
AMD FirePro W7100 8GB Graphics	Y	Y	J3G93AA	2
NVIDIA Quadro M6000 12GB Graphics	Y	Y	L2K02AA	2

For configurations not listed in this specification, please contact the factory for review

NOTE 1: 3rd and 4th graphics possible by using Option Kits.

NOTE 2: NVIDIA NVS 510 graphics available by using Option Kits only.

High Performance GPU Computing

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
NVIDIA Tesla K40 Workstation Coprocessor	Y	Y	F4A88AA	Note 1

NOTE 1:

Up to two K40 processors are supported.

Only supported with the Z840 1125W (1450W at 200V Input Voltage) Chassis.

Must have add-in graphics card in addition to the K40.

Supported Graphics cards are QK5200, QK6000, QK620, QK2200, QK4200, M6000.

Memory

CTO

DDR4-2133 ECC Registered DIMMs	Option Kit Part Number	Support Notes
4GB DDR4-2133 ECC Registered RAM	J9P81AA	
8GB DDR4-2133 ECC Registered RAM	J9P82AA	
16GB DDR4-2133 ECC Registered RAM	J9P83AA	
32GB DDR4-2133 ECC Load Reduced (LR) RAM	J9P84AA	

NOTES:

For details on the supported memory configurations on the HP Z840 Workstation, please refer to the System Technical Specifications - System Board section of this document.

DIMMs should be equally distributed across all four memory channels for optimal performance.

Each processor supports up to 4 channels of DDR4 memory. To realize full performance at least 1 DIMM must be inserted into each channel.

The CPUs determine the speed at which the memory is clocked. For example, if a 1600MT/s capable CPU is used in the system, the maximum speed the memory will run at is 1600MT/s regardless of the specified speed of the memory.

MT/s = Million Transfers per second

You cannot intermix LR DIMMs with Registered DIMMs. The system will not work.

The Z840 is designed to work ONLY with DDR4 memory. The system will not work with DDR3 memory.

Supported Components

Multimedia and Audio Devices

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Thin USB Powered Speakers	N	Y	KK912AA	
Integrated IDT 92HD94 Audio	Y	N	NA	

Optical and Removable Storage

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP DX115 Removable Drive Enclosure				
HP DX115 Removable HDD Frame/Carrier	N	Y	FZ576AA	Note 1
HP DX115 Removable HDD Carrier	Y	Y	NB792AA	Note 2
HP 15-in-1 Media Card Reader				
HP 15-in-1 Media Card Reader	Y	Y	F4N90AA	
HP SlimTray Optical Drives				
HP 9.5mm Slim SuperMulti DVD Writer	Y	Y	K3R64AA	
HP 9.5mm Slim DVD-ROM Drive	Y	Y	K3R63AA	Note 3
HP 9.5mm Slim BDXL Blu-Ray Writer	Y	Y	K3R65AA	Note 4

Actual speeds may vary. Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Double Layer discs can store more data than single-layer DVD drives and players.

In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation.

NOTE 1: Z840 support is for two DX115, in both of the 5.25" ODD bays.

NOTE 2: Carrier requires the workstation to have the DX115 frame installed. This part number is for the carrier only.

NOTE 3: Not supported as a 2nd Optical Drive

NOTE 4: Cannot be ordered in combination with another Blu-ray Writer drive.

Controller Cards

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP IEEE 1394b FireWire® PCIe Card	Y	Y	NK653AA	
HP Thunderbolt™-2 PCIe 1-port I/O Card*	Y	Y	F3F43AA	

Networking and Communications

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP X520 10GbE Dual Port Adapter	Y	Y	C3N52AA	

Supported Components

HP 10GbE SFP+ SR Transceiver	Y	Y	C3N53AA	
Intel Ethernet I210-T1 PCIe NIC	Y	Y	E0X95AA	
Intel 7260 802.11 a/b/g/n PCIe WLAN NIC	N	Y		
Integrated Intel I210AT PCIe GbE Controller	Y	N		Note 1
Integrated Intel I218LM PCIe GbE Controller	Y	N		Note 1
HP 361T PCIe Dual Port Gigabit NIC	Y	Y	C3N37AA	Note 1

NOTE 1: "Gigabit" or "GbE" Ethernet indicates compliance with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/sec. For high speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

*Wireless access point and internet service required. Availability of public wireless access points limited.

Racking and Physical Security

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
Security Cable with Kensington Lock	N	Y	PC766A	
HP Chassis Intrusion Sensor	Y	N		Standard on all systems
HP Z6/8 Adjustable Rail Rack Kit, Flush Mount	N	Y	B8S55AA	

Input Devices

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP USB Smart Card Keyboard	Y	Y	ED707AA	
HP 2.4GHz Wireless Keyboard & Mouse	N	Y	NB896AA	
HP USB Optical 3-Button 2.9M OEM Mouse	N	Y	ET424AA	
HP SpaceExplorer 3D USB Controller	N	Y	RY429AA	
HP SpacePilot 3D USB Intelligent Controller	N	Y	WH343AA	
HP PS/2 Keyboard	Y	Y	QY774AA	
HP PS/2 Mouse	Y	Y	QY775AA	
HP USB Keyboard	Y	Y	QY776AA	
HP USB Optical Mouse	Y	Y	QY777AA	
HP USB 1000dpi Laser Mouse	Y	Y	QY778AA	

Other Hardware

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Internal USB Port Kit	N	Y	EM165AA	Note 1
HP SAS Back Panel Connector Kit	N	Y	EM164AA	
HP eSATA PCI Cable Kit	Y	Y	GM110AA	Note 2
HP Power Cord Kit	Y	N		
HP Workstation Mouse Pad	Y	N		Japan Only
HP Optical Bay HDD Mounting Bracket	N	Y	NQ099AA	
HP ENERGY STAR® Qualified Configuration	Y	N		
HP 4-Bay SAS-SATA 2.5in High Density	Y	Y	K5J28AA	Note 3

Supported Components

Storage Kit

NOTE 1: The HP Internal USB Port kit has a single USB 2.0 type A connector.

NOTE 2: No hot plug / hot swap supported with eSATA

NOTE 3: The CTO option (J8J30AV) installs two of these kits to create room for 8 2.5" bays.

Software

	Factory Configured	Option Kit	Option Kit Part Number	Support Notes
HP Performance Advisor	Y	Y		Note 1
HP Remote Graphics Software (RGS) 6.0	Y	Y		Note 2
MS Office Home & Business 2013	Y	N		Note 3
Cyberlink PowerDVD and Power2Go	Y	N		
Foxit PhantomPDF Express	Y	N		

NOTE 1: Available as a free download here: www.hp.com/go/performanceadvisor

NOTE 2: Supports Windows 7, Windows 8.1, SLED 11, and RHEL v6.5

NOTE 3: Must be selected as a Configure to Order option. Delivered in the form of a "Drop in the Box" CD.

Operating Systems

	Support Notes
Genuine Windows® 7 Professional 64-bit	See note 1
HP Linux Installer Kit	
Red Hat Enterprise Linux (RHEL) Workstation - Paper License (1yr)	See note 2
Windows 8.1 Pro Downgrade to Windows 7 Professional 64-bit	
Windows 8.1 Pro 64-bit	
Windows 8.1 Pro Downgrade to Windows 7 Professional 64-bit (National Academic)	
Windows 8.1 Simplified Chinese Edition 64-bit	
Ubuntu 14.04	
Windows 8.1 Emerging Markets Single-Language 64-bit OS	

NOTE 1: See <http://www.microsoft.com/windows/windows-7/> for support details

NOTE 2: This second OS must be ordered with the HP Linux Installer Kit as the first OS.

System Technical Specifications

System Board



System Board Form Factor	Custom Form Factor, 13" x 14.25" (330.20mm x 361.95mm)
Processor Socket	Dual LGA2011-3
CPU Bus Speed	QPI: Up to 9.6GT/sec, dual link implementation
Chipset	Intel® C612 Chipset
Super I/O Controller	Nuvoton NPCD379H
Memory Expansion Slots	16 slots (8 slots per CPU)
Memory Type Supported	DDR4 R-DIMM (Registered), ECC: 4GB, 8GB, and 16GB DDR4 LR-DIMM (Load Reduced), ECC: 32GB (64GB and 128GB added after initial release)
Memory Modes	NUMA (Non-Uniform Memory Architecture), Memory Node Interleave
Memory Speed Supported	1600MT/s, 1866MT/s, and 2133MT/s

Single Processor										
CPU 0										
		Bottom Slots				Top Slots				
Capacity	Notes	DIMM1	DIMM2	DIMM3	DIMM4	DIMM5	DIMM6	DIMM7	DIMM8	Rating
4 GB	*	4 GB								Fair
8 GB		4 GB 8 GB							4 GB	Good Fair
12 GB	~	4 GB		4 GB					4 GB	Better
16 GB		4 GB 8 GB		4 GB			4 GB		4 GB 8 GB	Best Good
32 GB		4 GB 8 GB 16 GB	4GB	4 GB 8 GB	4 GB	4 GB	4 GB 8 GB	4 GB	4 GB 8 GB 16 GB	Best Best Good
48 GB	~	8 GB	4 GB	8 GB	4 GB	4 GB	8 GB	4 GB	8 GB	Best
64 GB		8 GB 16 GB	8 GB	8 GB 16 GB	8 GB	8 GB	8 GB 16 GB	8 GB	8 GB 16 GB	Best Best
96 GB	~	16 GB	8 GB	16 GB	8 GB	8 GB	16 GB	8 GB	16 GB	Best
128 GB		16 GB 32 GB	16 GB	16 GB 32 GB	16 GB	16 GB	16 GB 32 GB	16 GB	16 GB 32 GB	Best Best
256 GB	~	32 GB 64 GB	32 GB	32 GB 64 GB	32 GB	32 GB	32 GB 64 GB	32 GB	32 GB 64 GB	Best Best
512 GB	~ ~	64 GB 128 GB	64 GB	64 GB 128 GB	64 GB	64 GB	64 GB 128 GB	64 GB	64 GB 128 GB	Best Best
1 TB	~	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	Best
Slot Load Order		1	5	3	7	8	4	6	2	

System Technical Specifications

		Dual Processor																
		CPU 0								CPU 1								
		Bottom Slots				Top Slots				Bottom Slots				Top Slots				
Capacity	Notes	DIMM1	DIMM2	DIMM3	DIMM4	DIMM5	DIMM6	DIMM7	DIMM8	DIMM1	DIMM2	DIMM3	DIMM4	DIMM5	DIMM6	DIMM7	DIMM8	Rating
8 GB		4 GB								4 GB								Fair
16 GB		4 GB 8 GB							4 GB	4 GB 8 GB							4 GB	Good Fair
32 GB		4 GB 8 GB 16 GB		4 GB			4 GB		4 GB 8 GB	4 GB 8 GB 16 GB		4 GB			4 GB		4 GB 8 GB	Best Good Fair
64 GB		4 GB 8 GB	4 GB	4 GB 8 GB	4 GB	4 GB	4 GB 8 GB	4 GB	4 GB 8 GB	4 GB 8 GB	4 GB	4 GB 8 GB	4 GB	4 GB	4 GB 8 GB	4 GB	4 GB 8 GB	Best Best
96 GB	~	8 GB	4 GB	8 GB	4 GB	4 GB	8 GB	4 GB	8 GB	8 GB	4 GB	8 GB	4 GB	4 GB	8 GB	4 GB	8 GB	Best
128 GB	~	8 GB 16 GB 32 GB	8 GB	8 GB 16 GB	8 GB	8 GB	8 GB 16 GB	8 GB	8 GB 16 GB 32 GB	8 GB 16 GB 32 GB	8 GB	8 GB 16 GB	8 GB	8 GB	8 GB 16 GB	8 GB	8 GB 16 GB 32 GB	Best Best Good
192 GB	~	16 GB 16 GB	8 GB 16 GB	16 GB 16 GB	8 GB	8 GB	16 GB 16 GB	8 GB 16 GB	16 GB 16 GB	16 GB 16 GB	8 GB 16 GB	16 GB 16 GB	8 GB	8 GB	16 GB 16 GB	8 GB 16 GB	16 GB 16 GB	Best Better
256 GB		16 GB 32 GB	16 GB	16 GB 32 GB	16 GB	16 GB	16 GB 32 GB	16 GB	16 GB 32 GB	16 GB 32 GB	16 GB	16 GB 32 GB	16 GB	16 GB	16 GB 32 GB	16 GB	16 GB 32 GB	Best Best
512 GB	~	32 GB 64 GB	32 GB	32 GB 64 GB	32 GB	32 GB	32 GB 64 GB	32 GB	32 GB 64 GB	32 GB 64 GB	32 GB	32 GB 64 GB	32 GB	32 GB	32 GB 64 GB	32 GB	32 GB 64 GB	Best Best
1 TB	~	64 GB 128 GB	64 GB	64 GB 128 GB	64 GB	64 GB	64 GB 128 GB	64 GB	64 GB 128 GB	64 GB 128 GB	64 GB	64 GB 128 GB	64 GB	64 GB	64 GB 128 GB	64 GB	64 GB 128 GB	Best Best
2 TB	~	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	128 GB	Best
Slot Load Order		1	9	5	13	15	7	11	3	2	10	6	14	16	8	12	4	

System Technical Specifications

Memory Loading Order:	
<p>Load Order for Single Processor Configuration</p> 	<p>Load Order for Dual Processor Configuration</p> 
Maximum Memory	<p>Supports up to 256GB using RDIMMs</p> <p>Supports up to 1024GB using LRDIMMs</p> <p>Supports up to 2048GB using LRDIMMs</p>
Memory Configuration (Supported)	<ul style="list-style-type: none"> • Not all memory configurations possible are represented. Not all memory configurations shown are available as CTO. Please check Ordering Guide for supported configurations. • Only ECC DIMMs are supported. • RDIMM (Registered) and LR DIMM (Load Reduction) memory cannot be mixed. All memory installed in the system must be either RDIMM or LR DIMM. • Do not install memory modules into memory slots if corresponding processor is not installed. • Dual processor configurations with memory modules installed for only one processor is not supported.
Notes	<p>Please refer to the table above for details on how supported memory configurations are installed in your system.</p> <p>* For 32 bit operating systems, there is a memory limit of 4GB.</p> <p>~ Although technically possible, these configurations are not available to order at this time.</p> <p>The Z840 will support up to 512GB at initial release.</p> <p>The Z840 will support up to 1024GB when 64GB DIMM support is added following initial Z840 release.</p> <p>The Z840 will support up to 2048GB when 128GB DIMM support is added following initial Z840 release.</p>
PCI Express Connectors	<p>Two PCIe Gen3 x16 with latch</p> <p>One PCIe Gen3 x16 with latch.</p> <ul style="list-style-type: none"> • Enabled only with optional 2nd CPU is installed.

System Technical Specifications

	<p>One PCIe Gen3 x8 open-ended connector.</p> <ul style="list-style-type: none"> Enabled only with optional 2nd CPU is installed. <p>One PCIe x8 open-ended connector.</p> <ul style="list-style-type: none"> Enabled for One PCIe Gen2 x4 slot with 1 CPU Enabled for One PCIe Gen3 x8 with optional 2nd CPU installed <p>One PCIe Gen3 x4 open-ended connector.</p> <p>One PCIe Gen2 x1 open-ended connector</p>
Supported Drive Interfaces	
	<p>SATA</p> <p>2 SATA @6Gb/s, supports RAID 0,1 and NCQ. 4 sSATA @6Gb/s, Supports RAID 0,1,5,10 and NCQ. Factory integrated RAID is Microsoft Windows only.</p> <p>External SATA (eSATA)* Supported on all SATA and sSATA ports configurable with optional eSATA* After-Market Option cable kit) * hot plug / hot swap not supported with eSATA</p>
	<p>Serial Attached SCSI</p> <p>Integrated 8-channel SAS 6.0Gb/sec controller with HW RAID 0, 1, 10</p>
	<p>Integrated RAID</p> <p>SATA: RAID 0, 1 (Supports one RAID) SATA: RAID 0, 1, 5, 10 (Supports up to 2 RAIDs) SAS: HW RAID 0, 1, 10 (Supports up to 2 RAIDs)</p>
	<p>Integrated Graphics</p> <p>None</p>
	<p>Network Controller</p> <p>Integrated Intel I218LM</p> <p>Memory Integrated 3KB receive buffer and 3KB transmit buffer Data rates supported: 10/100/1000 Mb/s Compliance IEEE 802.1as, 802.1p, 802.1Q, 802.3, 802.3ab, 802.3az, 802.3i 802.3u, 802.3x, 802.3z Bus architecture PCIe 1.0 x1 and SMBus Power requirement 0.5 watts Boot ROM support Network transfer rates: 10BASE-T (half-duplex) 10 Mb/s 10BASE-T (full-duplex) 20 Mb/s 100BASE-TX (half-duplex) 100 Mb/s 100BASE-TX (full-duplex) 200 Mb/s 1000BASE-T (full-duplex) 2000 Mb/s Management capabilities: WOL, auto MDI crossover, PXE, Multi-port teaming, RSS, Advanced cable diagnostics</p> <p>AMT 9.1 support, vPro compliant</p> <p>Integrated I210AT</p> <p>Adjustable FIFO packet buffer memory up to 24KB Tx, 16KB Rx Data rates supported 10/100/1000 Mb/s Compliance IEEE 802.1as, 802.1q, 802.1Q, 802.3, 802.3ab, 802.3ap, 802.3az, 802.3u, 802.3x, 802.3z</p>

System Technical Specifications

		<p>Bus architecture PCIe 1.0 x1 and SMBus</p> <p>Boot ROM support</p> <p>Network transfer rates:</p> <ul style="list-style-type: none"> 10BASE-T (half-duplex) 10 Mb/s 10BASE-T (full-duplex) 20 Mb/s 100BASE-TX (half-duplex) 100 Mb/s 100BASE-TX (full-duplex) 200 Mb/s 1000BASE-T (full-duplex) 2000 Mb/s <p>Management capabilities: WOL, auto MDI crossover, PXE, Multi-port teaming, RSS, Advanced cable diagnostics</p>
	PCI-X Connectors	None
	PCI Card Guide	Yes
	Wake on LAN	Yes, both ports
	Integrated Trusted Platform Module	Infineon TPM 1.2 Certified (TPM2.0 Certified, Hardware Enabled; Not Available at Initial Release)
IEEE 1394 Connector(s)	Front	None
	Rear	None
	Internal	None
USB Connector(s)	Front	4 USB 3.0
	Rear	4 USB 3.0 2 USB 2.0
	Internal	<p>1 USB 3.0 available with a single 20-pin shrouded connector. This header supports a USB Media Card reader.</p> <p>2 USB 2.0 port available with one 2x5 header. This header supports an HP Internal USB Port Kit (EM165AA) to provide a single USB Type-A connector. This port kit uses one half of the 2x5 header.</p> <p>Third party adapters are also available.</p>
HD Integrated Audio	Realtek ALC221	
Flash ROM	Yes	
CPU Fan Header	One header (blind mate) for CPU fans and memory fans	
Chassis Fan Header	One Chassis Fan Header	
Front PCI Fan Header	2 Front PCI Fan Headers	
Front Control Panel/Speaker Header	Yes	
CMOS Battery Holder - Lithium	Yes	
Power Supply Headers	Yes	
Power Switch, Power LED & Hard Drive LED Header	Front power switch, front power and hard drive LED. Rear power switch and rear power LED. Drive LED header on system board.	
Clear Password Jumper	Yes	
Serial Port	Yes, on rear panel	
Parallel Port	No	
Keyboard/Mouse	Yes	
Power Supply	850W 88% Efficient, Custom PSU	1125W/1275W*/1450W*

System Technical Specifications

	(Wide-Ranging, Active PFC)		90% Efficient, Custom PSU (Wide-Ranging, Active PFC)	
Operating Voltage Range	90-269 VAC		90-269 VAC	
Rated Voltage Range	100-127 VAC 200-240 VAC	118 VAC	Rated Voltage Range	100 VAC 115-127 VAC 200-240 VAC
Rated Line Frequency	50-60 Hz	400 Hz	Rated Line Frequency	50-60 Hz
Operating Line Frequency Range	47-66 Hz	393-407 Hz	Operating Line Frequency Range	47-66 Hz
Rated Input Current	11A @ 100-127 VAC 5.5A @ 200-240 VAC	11A @ 118 VAC	Rated Input Current	11A @ 100-127 VAC 5.5A @ 200-240 VAC
Heat Dissipation (Configuration and software dependent)	Typical = 2142 btu/hr (540kg-cal/hr) Max = 3335 btu/hr (840 kg-cal/hr)		Typical = 2773 btu/hr (699 kg-cal/hr) Max-1 = 3878 btu/hr (977 kg-cal/hr) Max-2 = 5002 btu/hr (1260 kg-cal/hr) Max-3 = 5624 btu/hr (1417 kg-cal/hr)	
Power Supply Fan	(2) 80x25 mm variable speed		(2) 80x25 mm variable speed	
ENERGY STAR Qualified (Configuration dependent)	Yes		Yes	
Power Supply Efficiency	88% Efficient The Z840 850W power supply efficiency report can be found at this link: http://www.plugloadsolutions.com/psu_reports/HEWLETT%20PACKARD_719798-001_850W_ECOS%203882_Report.pdf		90% Efficient The Z840 1125W (1450W at 200V Input Voltage) power supply efficiency report can be found at this link: http://www.plugloadsolutions.com/psu_reports/HEWLETT%20PACKARD_719799-001_1125W_ECOS%203883_Report.pdf	
FEMP Standby Power Compliant @115V (<2W in S5 - Power Off)	Yes		Yes	
EuP Compliant @ 230V (<0.5 W in S5 - Power Off)	Yes		Yes	
CECP Compliant @ 220V (<4W in S3 - Suspend to RAM)	Yes; Configuration dependent		Yes; Configuration dependent	
Power Consumption in sleep mode (as defined by ENERGY STAR) - Suspend to RAM (S3) (Instantly Available PC)	<23W		<30W	
Built-in Self-Test LED	Yes		Yes	
Surge Tolerant Full Ranging Power Supply (withstands power surges up to 2000V)	Yes		Yes	
	*Input voltage restriction			
	<p>NOTE: The 1125W (1450W at 200V Input Voltage) power supply can also supply 1275W of output power when the input voltage is greater than 105V. If the input voltage is less than 105V, but greater than 90V for any reason, the maximum power that can be drawn is 1125W. An uninterruptible power supply (UPS) is highly recommended if 1275W output power is desired.</p> <p>The 1125W Power Supply can also supply 1450W of output power when the input voltage is</p>			

System Technical Specifications

	greater than 180V under all conditions.
AUX IN (audio)	No
Clear CMOS Button	Yes
Multibay Header	No
Integrated Gigabit Ethernet	Yes, dual port.
Access Panel Solenoid Lock Header	No
Access Panel Intrusion Sensor Header	Yes, as part of Front UI (Control Panel) cable header
Memory Fan Connector	Yes, blind-mate

SYSTEM CONFIGURATION

Example Configuration #1	Processor Info	1x Intel Xeon E5-2609v3 (Six-Core) 85W					
	Memory Info	16GB DDR4-2133 (2x8GB) 1CPU RegRAM					
	Graphics Info	1x NVIDIA Quadro K620					
	Disks/Optical/Floppy	1x 500GB SATA 7200/1x DVD-ROM SATA					
	Power Supply	850W 88% Custom PSU					
	Other	-					
Energy Consumption		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	103.41 W		102.23 W		103.92 W	
	Windows Busy Typ (S0)	183.75 W		181.88 W		189.37 W	
	Windows Busy Max (S0)	204.93 W		201.28 W		206.74 W	
	Sleep (S3)	3.711 W	3.587 W	3.785 W	3.711 W	3.587 W	3.785 W
	Off (S5)	1.053 W	0.992 W	1.159 W	1.053 W	0.992 W	1.159 W
	Zero Power Mode (ErP)	0.182 W		0.298 W		0.172 W	
Heat Dissipation** (Btu/hr)		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	352.83 btu/hr		348.81 btu/hr		354.58 btu/hr	
	Windows Busy Typ (S0)	626.96 btu/hr		620.57 btu/hr		646.13 btu/hr	
	Windows Busy Max (S0)	699.22 btu/hr		686.77 btu/hr		705.40 btu/hr	
	Sleep (S3)	12.66 btu/hr	12.24 btu/hr	12.91 btu/hr	12.66 btu/hr	12.24 btu/hr	12.91 btu/hr
	Off (S5)	3.59 btu/hr	3.38 btu/hr	3.95 btu/hr	3.59 btu/hr	3.38 btu/hr	3.95 btu/hr
	Zero Power Mode (ErP)	0.621 btu/hr		1.018 btu/hr		0.586 btu/hr	

Example Configuration #2 (ENERGY STAR QUALIFIED)	Processor Info	2x Intel Xeon E5-2640v3 (Eight-Core) 90W					
	Memory Info	32GB DDR4-2133 (8x4GB) 2CPU RegRAM					
	Graphics Info	1x NVIDIA Quadro K2200					
	Disks/Optical/Floppy	3x 500GB SATA 7200/1x DVD-ROM SATA					
	Power Supply	1125W (1450W at 200V Input Voltage) 90% Custom PSU					
	Other	-					
Energy Consumption		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	Windows Idle (S0)	1242.17 W		141.01 W		142.47 W	

System Technical Specifications

	Windows Busy Typ (S0)	324.18 W		320.33 W		323.91 W		
	Windows Busy Max (S0)	398.27 W		396.25 W		398.75 W		
	Sleep (S3)	6.08 W	6.03 W	6.13 W	6.08 W	6.03 W	6.13 W	
	Off (S5)	1.04 W	0.99 W	1.10 W	1.04 W	0.99 W	1.10 W	
	Zero Power Mode (ErP)	0.181 W		0.308 W		0.172 W		
Heat Dissipation** (Btu/hr)		115 VAC		230 VAC		100 VAC		
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	
		Windows Idle (S0)	485.08 btu/hr		481.13 btu/hr		486.11 btu/hr	
		Windows Busy Typ (S0)	1106.10 btu/hr		1092.97 btu/hr		1105.18 btu/hr	
		Windows Busy Max (S0)	1358.90 btu/hr		1352.01 btu/hr		1360.54 btu/hr	
		Sleep (S3)	20.75 btu/hr	20.57 btu/hr	20.91 btu/hr	20.75 btu/hr	20.57 btu/hr	20.91 btu/hr
		Off (S5)	3.55 btu/hr	3.38 btu/hr	3.76 btu/hr	3.55 btu/hr	3.38 btu/hr	3.76 btu/hr
		Zero Power Mode (ErP)	0.619 btu/hr		1.051 btu/hr		0.587 btu/hr btu/hr	

Example Z840 Configuration #3	Processor Info	2x Intel Xeon E5-2680v3 (12-Core) 120W					
	Memory Info	64GB DDR4-2133 (8x8GB) 2CPU RegRAM					
	Graphics Info	1x NVIDIA Quadro K4200					
	Disks/Optical/Floppy	2x 300GB SAS 15K/1x SuperMulti DVDRW SATA					
	Power Supply	1125W (1450W at 200V Input Voltage) 90% Custom PSU					
	Other	-					

Energy Consumption		115 VAC		230 VAC		100 VAC		
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	
		Windows Idle (S0)	123.26 W		121.40 W		124.07 W	
		Windows Busy Typ (S0)	413.33 W		393.34 W		412.26 W	
		Windows Busy Max (S0)	496.46 W		483.26 W		498.07 W	
		Sleep (S3)	7.114 W	7.086 W	7.148 W	7.114 W	7.086 W	7.148 W
		Off (S5)	1.054 W	0.993 W	1.161 W	1.054 W	0.993 W	1.161 W
		Zero Power Mode (ErP)	0.181 W		0.307 W		0.177 W	

Heat Dissipation** (Btu/hr)		115 VAC		230 VAC		100 VAC		
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	
		Windows Idle (S0)	420.56 btu/hr		414.22 btu/hr		423.33 btu/hr	
		Windows Busy Typ (S0)	1410.28 btu/hr		1342.08 btu/hr		1406.63 btu/hr	
		Windows Busy Max (S0)	1693.95 btu/hr		1648.88 btu/hr		1700.10 btu/hr	
		Sleep (S3)	24.27 btu/hr	24.17 btu/hr	24.39 btu/hr	24.27 btu/hr	24.17 btu/hr	24.39 btu/hr
		Off (S5)	3.597 btu/hr	3.388 btu/hr	3.962 btu/hr	3.597 btu/hr	3.388 btu/hr	3.962 btu/hr
		Zero Power Mode (ErP)	0.619 btu/hr		1.049 btu/hr		0.607 btu/hr btu/hr	

Example Z840 Configuration #4	Processor Info	2x Intel Xeon E5-2697v3 (14-Core) 145W					
	Memory Info	64GB DDR4-2133 (16x4GB) 2CPU RegRAM					
	Graphics Info	2x NVIDIA Quadro K5200					
	Disks/Optical/Floppy	4x 300GB SAS 15K/1x SuperMulti DVDRW SATA					

System Technical Specifications

	Power Supply	1125W (1450W at 200V Input Voltage) 90% Custom PSU							
	Other	-							
Energy Consumption		115 VAC		230 VAC		100 VAC			
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled		
	Windows Idle (S0)	141.75 W		140.45 W		141.63 W			
	Windows Busy Typ (S0)	510.66 W		498.90 W		510.82 W			
	Windows Busy Max (S0)	569.34 W		559.38 W		568.48 W			
	Sleep (S3)	6.454 W	3.669 W	6.497 W	6.454 W	3.669 W	6.497 W		
	Off (S5)	1.105 W	0.987 W	1.165 W	1.105 W	0.987 W	1.165 W		
	Zero Power Mode (ErP)	0.180 W		0.306 W		0.178 W			
Heat Dissipation** (Btu/hr)		LAN Enabled		LAN Disabled		LAN Enabled		LAN Disabled	
	Windows Idle (S0)	483.65 btu/hr		497.22 btu/hr		483.24 btu/hr			
	Windows Busy Typ (S0)	1742.37 btu/hr		1702.25 btu/hr		1742.91 btu/hr			
	Windows Busy Max (S0)	1942.29 btu/hr		1908.60 btu/hr		1939.65 btu/hr			
	Sleep (S3)	22.02 btu/hr	21.63 btu/hr	22.16 btu/hr	22.02 btu/hr	21.63 btu/hr	22.16 btu/hr		
	Off (S5)	3.77 btu/hr	3.37 btu/hr	3.97 btu/hr	3.77 btu/hr	3.37 btu/hr	3.97 btu/hr		
	Zero Power Mode (ErP)	0.616 btu/hr		1.046 btu/hr		0.608 btu/hr			

Example Configuration #5 (ENERGY STAR QUALIFIED)	Processor Info	2x Intel Xeon 2687Wv3 (10-Core) 160W					
	Memory Info	512GB DDR4-2133 (16x32GB) 2CPU LR RAM					
	Graphics Info	2x NVIDIA Quadro K6000					
	Disks/Optical/Floppy	6x 300GB 10K SAS SFF/1x SuperMulti DVDRW SATA					
	Power Supply	1125W (1450W at 200V Input Voltage) 90% Custom PSU					
	Other	-					
Energy Consumption		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	On-Idle (ENERGY STAR® Idle (S0))	174.56 W		173.77 W		175.26 W	
	ENERGY STAR® P _{MAX} Windows running Linpack and Viewperf	561.98 W		559.23 W		567.75 W	
	ENERGY STAR® "Sleep" (S3)	16.426 W	16.279 W	16.099 W	16.426 W	16.279 W	16.099 W
	ENERGY STAR® "Standby" (Off) (S5)	1.047 W	0.997 W	1.144 W	1.047 W	0.997 W	1.144 W
Heat Dissipation** (Btu/hr)		115 VAC		230 VAC		100 VAC	
		LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled	LAN Enabled	LAN Disabled
	On-Idle (ENERGY STAR® Idle (S0))	595.60 btu/hr		592.90 btu/hr		597.99 btu/hr	
	ENERGY STAR® P _{MAX} Windows running Linpack and Viewperf	1917.48 btu/hr		1908.09 btu/hr		1937.16 btu/hr	
	ENERGY STAR® "Sleep" (S3)	56.046 btu/hr	55.545 btu/hr	54.935 btu/hr	56.046 btu/hr	55.545 btu/hr	54.935 btu/hr

System Technical Specifications

DECLARED NOISE EMISSIONS (ENTRY-LEVEL AND HIGH-END CONFIGURATIONS)

System Configuration (Entry level)	Processor Info	-
	Memory Info	-
	Graphics Info	-
	Disks/Optical/Floppy	-

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	-	-
	Hard drive Operating (random reads)	-	-
	DVD-ROM Operating (sequential reads)	-	-

System Configuration (High-end)	Processor Info	-
	Memory Info	-
	Graphics Info	-
	Disks/Optical/Floppy	-

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)		Sound Power (LWAd, bels)	Deskside Sound Pressure (LpAm, decibels)
	Idle	-	-
	Hard drive Operating (random reads)	-	-
	DVD-ROM Operating (sequential reads)	-	-

ENVIRONMENTAL DATA

Environmental Requirements	Temperature	Operating: 5° to 35° C (40° to 95° F) Non-operating: -40° to 60° C (-40° to 140° F)
	Humidity	Operating: 8% to 85% RH, non-condensing Non-operating: 8% to 90% RH, non-condensing
	Maximum Altitude	Operating: 3,000 m (10,000 feet) Non-operating: 9,100 m (30,000 feet)
	Dynamic (new)	Shock Operating: ½-sine: 40g, 2-3ms (~62 cm/sec) Non-operating: ½-sine: 160 cm/s, 2-3ms (~105g) square: 422 cm/s, 20g NOTE: Values represent individual shock events and do not indicate repetitive shock events.

System Technical Specifications

		<p>Vibration</p> <p>Operating random: 0.5g (rms), 5-300 Hz, up to 0.0025 g²/Hz</p> <p>Non-operating random: 2.0g (rms), 5-500 Hz, up to 0.0150 g²/Hz</p> <p>NOTE: Values do not indicate continuous vibration.</p>
	Cooling	Above 1524 m (5000 ft.) altitude, maximum operating temperature is de-rated by 1° C (1.8° F) per 305 m (1000 ft.) elevation increase

PHYSICAL SECURITY AND SERVICEABILITY

Access Panel	Tool-less Includes system board and memory information
Optical Drive	Tool-less, no carrier or rails required
Hard Drives	Tool-less
Expansion Cards	Tool-less
Processor Socket	Tool-less
Green User Touch Points	Yes, on tool-free internal chassis components
Color-coordinated Cables and Connectors	Yes
Memory	Tool-less
System Board	Tool-less, retained by Front PCI Card Guide
Dual Color Power and HD LED on Front of Computer	Yes
Configuration Record SW	Yes
Over-Temp Warning on Screen	Yes
Restore CD/DVD Set	Restores the computer to its original factory shipping image - Can be obtained via HP Support
Dual Function Front Power Switch	Yes, causes a fail-safe power off when held for 4 seconds
Padlock Support	No
Cable Lock Support	Yes, Kensington Cable Lock (optional): Prevents entire system theft only. 3mm x 7mm slot at rear of system
Universal Chassis Clamp Lock Support	No
Solenoid Lock and Hood Sensor	No
Rear Port Control Cover	No
Serial, Parallel, USB, Audio, Network, Enable/Disable Port Control	Yes
Removable Media Write/Boot Control	Yes, prevents ability to boot from removable media on supported devices (and can disable writes to media)
Power-On Password	Yes, prevents an unauthorized person from booting up the workstation
Setup Password	Yes, prevents an unauthorized person from changing the workstation configuration
3.3V Aux Power LED on System PCA	No
NIC LEDs (integrated)	Yes

System Technical Specifications

(Green & Amber)	
CPUs and Heatsinks	A torx driver (T15) is needed to remove the CPU heatsink(s) before the CPU can be removed. CPU removal is tool-less
Power Supply Diagnostic LED	Yes
Front Power Button	Yes
Front Power LED	Yes, white (normal), red (fault)
Front Hard Drive Activity LED	Yes, white
Front ODD Activity LED	Yes
Internal Speaker	Yes
System/Emergency ROM Flash Recovery	Recovers corrupted system BIOS
Cooling Solutions	Air cooled forced convection
Power Supply Fans	2x - 80mm x 25mm
CPU Heatsink Fan	92 x 25mm 5-wire PWM for each CPU
Chassis Fan	Rear: 2x - 92mm x 25mm Front (850W config): 1x - 92mm x 25mm (upper position) Front (1125W (1450W at 200V Input Voltage) config): 2x - 92mm x 25mm
Memory Heatsink Fan	3x - 75 x 90 x 35mm memory blowers 80 x 25 mm 4-wire PW fan
HP Vision Diagnostics Offline Edition	<p>HP Vision Diagnostics Offline Edition</p> <p>The diagnostics utility enables you to perform testing and to view critical computer hardware and software configuration information from various sources. This utility enables you to:</p> <ul style="list-style-type: none"> • Run diagnostics • View the hardware configuration of the system <p>Key features and benefits</p> <p>HP Vision Diagnostics simplifies the process of effectively identifying, diagnosing, and isolating the hardware issues. In addition to robust management tools, service tools can be invaluable in quickly resolving system problems. To streamline the service process and resolve problems quickly, it is necessary to have the right information available at the time that a service call is placed. The primary information requirement, which is also the one that provides the greatest Vision into potential system issues, is the configuration of the system. Vision Diagnostics helps provide higher system availability. Typical uses of the Vision Diagnostics are:</p> <ul style="list-style-type: none"> • Testing and diagnosing apparent hardware failures • Documenting system configurations for upgrade planning, standardization, inventory tracking, disaster recovery, and maintenance • Sending configuration information to another location for more in-depth analysis
Access Panel Key Lock	Yes, prevents removal of the access panel and all internal components including optical and floppy drives
ACPI-Ready Hardware	Advanced Configuration and Power Management Interface (ACPI). <ul style="list-style-type: none"> • Allows the system to wake from a low power mode. • Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the

System Technical Specifications

	system
Trusted Platform Module Chip	Yes
Integrated Chassis Handles	Yes, front and rear
Power Supply	Tool-less, direct-connect (blind-mate)
PCIe Card Retention	Yes, rear (all), middle (full-height cards), front (full-length with extender cards)
Flash ROM	Yes. SPI ROM
Diagnostic Power Switch LED on board	Yes
Clear Password Jumper	Yes
Clear CMOS Button	Yes
CMOS Battery Holder	Yes
DIMM Connectors	Yes

BIOS

BIOS 32-bit Services	Standard BIOS 32-Bit Service Directory Proposal v0.4. BIOS supports 32 and 64-bit Operating systems.
PCI 3.0 Support	Full BIOS support for PCI Express through industry standard interfaces.
ATAPI	ATAPI Removable Media Device BIOS Specification Version 1.0.
BBS	BIOS Boot Specification v1.01
WMI Support	WMI is Microsoft's implementation of Web-Based Enterprise Management (WBEM) for Windows. WMI is fully compliant with the Distributed Management Task Force (DMTF) Common Information Model (CIM) and WBEM specifications.
BIOS Boot Spec 1.01+	Provides more control over how and from what devices the workstation will boot.
BIOS Power On	Users can define a specific date and time for the system to power on.
ROM Based Computer Setup Utility (F10)	Review and customize system settings controlled by the BIOS.
System/Emergency ROM Flash Recovery with Video	Recovers system BIOS in corrupted Flash ROM.
Replicated Setup	Saves BIOS settings to diskette or USB flash drive in human readable file. Repset.exe utility can then replicate these settings on machines being deployed without entering Computer Configuration Utility (F10 setup).
SMBIOS	System Management BIOS 2.7, for system management information
Boot Control	Disables the ability to boot from removable media on supported devices.
Memory Change Alert	Alerts management console if memory is removed or changed.
Thermal Alert	Monitors the temperature state within the chassis. Three modes: - NORMAL - normal temperature ranges. - ALERTED - excessive temperatures are detected. Raises a flag so action can be taken to avoid shutdown or provide for a smoother system shutdown. - SHUTDOWN - excessive temperatures are encountered. Automatically shuts down the computer without warning before hardware component damage occurs.
Remote ROM Flash	Provides secure, fail-safe ROM image management from a central network console.

System Technical Specifications

ACPI (Advanced Configuration and Power Management Interface)	Allows the system to enter and wake from low power modes (sleep states). Enables an operating system to control system power consumption based on the dynamic workload. Makes it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system. Supports ACPI 4.0 for full compatibility with 64-Bit operating systems.
Ownership Tag	A user-defined string stored in non-volatile memory that is displayed in the BIOS splash screen.
Remote Wakeup/Remote Shutdown	System administrators can power on, restart, and power off a client computer from a remote location.
Instantly Available PC (Suspend to RAM - ACPI sleep state S3)	Allows for very low power consumption with quick resume time.
Remote System Installation via F12 (PXE 2.1) (Remote Boot from Server)	Allows a new or existing system to boot over the network and download software, including the operating system.
ROM revision levels	Reports the system BIOS revision level in Computer Configuration Utility (F10 Setup). Version is available through an industry standard interface (SMBIOS) so that management SW applications can use and report this information.
System board revision level	Allows management SW to read the revision level of the system board Revision level is digitally encoded into the HW and cannot be modified.
Start-up Diagnostics (Power-on Self-Test)	Assesses system health at boot time with selectable levels of testing.
Auto Setup when new hardware installed	System automatically detects addition of new hardware.
Keyboard-less Operation	The system can be booted without a keyboard.
Localized ROM Setup	Common BIOS image supports System Configuration Utility (F10 Setup) menus in 12 languages with local keyboard mappings.
Asset Tag	Allows the user or MIS to set a unique tag string in non-volatile memory.
Per-slot Control	Allows I/O slot parameters (option ROM enable/disable, bus latency) to be configured individually.
Adaptive Cooling	Fan control parameters are set according to detected hardware configuration for optimal acoustics.
Pre-boot Diagnostics	Early (pre-video) critical errors are reported via beeps and blinks on the power LED.
Industry Standard Specification Support	
Industry Standard	Revision Supported by the BIOS
UEFI Specification Revision	2.3.1
ACPI	Advanced Configuration and Power Management Interface, Version 4.0
ATA (IDE)	AT Attachment 6 with Packet Interface (ATA/ATAPI-6), Revision 3b
CD Boot	"El Torito" Bootable CD-ROM Format Specification Version 1.0
EDD	- Enhanced Disk Drive Specification Version 1.1 - BIOS Enhanced Disk Drive Specification Version 3.0
EHCI	Enhanced Host Controller Interface for Universal Serial Bus, Revision 1.0
PCI	- PCI Local Bus Specification, Revision 2.3 - PCI Power Management Specification, Revision 1.1 - PCI Firmware Specification, Revision 3.0, Draft .7
PCI Express	PCI Express Base Specification, Revision 2.0 PCI Express Base Specification, Revision 3.0

System Technical Specifications

PMM	POST Memory Manager Specification, Version 1.01
SATA	Serial ATA Specification, Revision 1.0a Serial ATA 3 Gb/s: Serial ATA Specification, Revision 2.5 Serial ATA 6 Gb/s: Serial ATA Specification, Revision 3.0
SPD	PC SDRAM Serial Presence Detect (SPD) Specification, Revision 1.2B
TPM	Trusted Computing Group TPM Specification Version 1.2
UHCI	Universal Host Controller Interface Design Guide, Revision 1.1
USB	Universal Serial Bus Revision 1.1 Specification Universal Serial Bus Revision 2.0 Specification Universal Serial Bus Revision 3.0 Specification
SMBIOS	System Management BIOS Reference Specification, Version 2.7
	External BIOS Simulator found at: http://h20464.www2.hp.com/index.html

External BIOS Simulator found at: <http://h20464.www2.hp.com/index.html>

Social and Environmental Responsibility

Eco-Label Certifications & Declarations	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: <ul style="list-style-type: none"> ENERGY STAR® (energy-saving features available on selected configurations-Windows only) US Federal Energy Management Program (FEMP) China Energy Conservation Program <i>The ECO Declaration (TED)</i>
Batteries	The battery in this product complies with EU Directive 2006/66/EC Battery size: CR2032 (coin cell) Battery type: Lithium Metal The battery in this product does not contain: <ul style="list-style-type: none"> Mercury greater than 5ppm by weight Cadmium greater than 10ppm by weight Lead greater than 40ppm by weight
Restricted Material Usage	This product meets the material restrictions specified in HP's General Specification for the Environment. http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis.
Low Halogen Statement	This product is low halogen except for power cords, cables and peripherals, as well as the following customer-configurable internal components: 3 ½" SAS HDDs, LSI 9260-8i SAS 6Gb/s ROC RAID Card, Creative Recon3D PCIe Audio Card, Liquid Cooling Solution and Broadcom 5761 Gigabit PCIe NIC are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
End-of-Life Management and Recycling	Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner. This product is greater than 90% recyclable by weight when properly disposed of at end of life.

System Technical Specifications

Hewlett-Packard Corporate Environmental Information	<p>For more information about HP's commitment to the environment: Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/qcreport/index.html</p> <p>Eco-label certifications http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html</p> <p>ISO 14001 certificates: http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html</p>
Additional Information	<ul style="list-style-type: none"> • This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC. • Plastic parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043. • This product is >90% recycle-able when properly disposed of at end of life. <p>EPEAT Gold - ENERGY STAR qualified configurations of this product are in compliance with the IEEE 1680 (EPEAT) standard at the Gold level where HP registers workstation products. See http://ww2.epeat.net/CompanyDetail.aspx?CompanyID=24 for registration status in your country.</p>
Packaging	<p>HP Workstation product packaging meets the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/society/gen_specifications.html</p> <ul style="list-style-type: none"> • Does not contain restricted substances listed in HP Standard 011-1 General Specification for the Environment • Does not contain ozone-depleting substances (ODS) • Does not contain heavy metals (lead, mercury, cadmium or hexavalent chromium) in excess of 100 ppm sum total for all heavy metals listed • Maximizes the use of post-consumer recycled content materials in packaging materials • All packaging material is recyclable • All packaging material is designed for ease of disassembly • Reduced size and weight of packages to improve transportation fuel efficiency • Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards formatting
Packaging Materials	
Internal	<p>Cushions and plastic bags made of low density polyethylene (LDPE).</p>
External	<p>Outer carton, accessories carton, and insert made of corrugated paper board.</p>

MANAGEABILITY

Industry Standard Specifications	<p>This product meets the following industry standard specifications for manageability functionality:</p> <ul style="list-style-type: none"> • DASH 1.1 (via Intel LAN on motherboard)
Intel Active Management Technology (AMT)	<p>Intel® Active Management Technology (AMT) 9.1</p> <p>An advanced set of remote management features and functionality providing IT administrators the latest and most effective tools to remotely discover, heal, and protect networked client systems regardless of the system's health or power state. AMT 9.1 includes the following advanced management functions:</p> <ul style="list-style-type: none"> • Power Management (on, off, reset, graceful shutdown, sleep and hibernate) • Support in Max Power Savings (Shutdown and Hibernate Modes) • Hardware Inventory (includes BIOS and firmware revisions)

System Technical Specifications

	<ul style="list-style-type: none"> • Hardware Alerting • Agent Presence • System Defense Filters • Serial Over LAN (SOL) • IDE Redirect • ME Wake-on-LAN (WOL) • DASH 1.1 compliance • IPv6 Support • Fast Call for Help - a client inside or outside the firewall may initiate a call for help via BIOS screen, periodic connections, or alert triggered connection • Remote Scheduled Maintenance - pre-schedule when the system connects to the IT or service provider console for maintenance. • Remote Alerts - automatically alert IT or service provider if issues arise • Access Monitor - Provides oversight into Intel® AMT actions to support security requirements • PC Alarm Clock • Microsoft NAP Support • Host Base set-up and configuration • Management Engine (ME) firmware roll back • Local Time Sync to UTC Remote Memory Dump Command – Creates memory dump for debug
Intel® vPro™ Technology	<p>The HP Z840 Workstation supports Intel vPro technology when configured as outlined below:</p> <ul style="list-style-type: none"> • Intel® Xeon® processor E5-1600 v3 product family or E5-2600 v3 product family featuring Intel® vPro™ Technology • Intel® C610 chipset • Intel® I218LM GbE LAN
Remote Manageability Software Solutions	<p>The HP Z840 Workstation is supported on the following remote manageability software consoles:</p> <ul style="list-style-type: none"> • LANDesk Management Suite (HP recommended solution) • Microsoft System Center Configuration Manager • HP Client Automation Enterprise <p>For questions or support for manageability needs, please visit http://www.hp.com/go/easydeploy</p>
System Software Manager	<p>For questions or support for SSM, please visit: http://www.hp.com/go/ssm</p>
Service, Support, and Warranty	<p>On-site Warranty and Service (Note 1): Three-years, limited warranty and service offering delivers on-site, next business-day (Note 2) service for parts and labor and includes free telephone support (Note 3) 8am - 5pm. Global coverage (Note 2) ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering.</p> <p>NOTE 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply. NOTE 2: On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country. NOTE 3: Technical telephone support applies only to HP-configured, HP and HP-qualified, third-party hardware and software. Toll-free calling and 24x7 support service may not be available in some countries.</p> <p>HP Care Pack Services are extended service contracts that go beyond the standard limited warranties. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/lookuptool. Additional HP Care</p>

System Technical Specifications

	<p>Pack Services information by product is available at: http://www.hp.com/hps/carepack. Service levels and response times for HP Care Packs may vary depending on your geographic location. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.</p>
Product Change Notification	<ul style="list-style-type: none">• Program to proactively communicate Product Change Notifications (PCNs) and Customer Advisories by email to customers, based on a user-defined profile.• PCNs provide advance notification of hardware and software changes to be implemented in the factory providing time to plan for transition.• Customer Advisories provide concise, effective problem resolution, greatly reducing the need to call technical support.

Stable & Consistent Offerings

Global Series SKUs

As part of its commitment to hardware, software, and solution innovation, HP is proud to introduce this breakthrough platform configuration stability to HP Workstation customers. HP Stable & Consistent Offerings are built on the foundation of a carefully chosen set of hardware and software designed and tested to work with all HP Z Workstation platforms through their end of life. These components and their corresponding HP Workstation platform compatibility are outlined in this section.

HP Stable & Consistent Offerings are available worldwide to all HP Workstation customers—no special programs, no additional cost—no kidding. Simply select your hardware and software components when you customize your HP Workstation and be assured that you'll be able to buy that same configuration throughout the lifecycle of the product.

Processors

Product #	Offering
J6F75AV	Intel Xeon E5-2620v3 2.4 1866 6C 1stCPU
J6F73AV	Intel Xeon E5-2630v3 2.4 1866 8C 1stCPU
J6F71AV	Intel Xeon E5-2637v3 3.5 2133 4C 1stCPU
J6F94AV	Intel Xeon E5-2620v3 2.4 1866 6C 2ndCPU
J6F92AV	Intel Xeon E5-2630v3 2.4 1866 8C 2ndCPU
J6F90AV	Intel Xeon E5-2637v3 3.5 2133 4C 2ndCPU

Hard Drives

Product #	Offering
J3K71AV	500GB 7200 RPM SATA 1st HDD
J3K72AV	1TB 7200 RPM SATA 1st HDD
J3K92AV	500GB 7200 RPM SATA 2nd HDD
J3K93AV	1TB 7200 RPM SATA 2nd HDD
J3L13AV	500GB 7200 RPM SATA 3rd HDD
J3L14AV	1TB 7200 RPM SATA 3rd HDD
J3L36AV	500GB 7200 RPM SATA 4th HDD
J3L37AV	1TB 7200 RPM SATA 4th HDD
J3L54AV	500GB 7200 RPM SATA 5th HDD
J3L55AV	1TB 7200 RPM SATA 5th HDD

Graphics

Product #	Offering
J1Q20AV	NVIDIA Quadro K2200 4GB 1st GFX
J1Q24AV	AMD FirePro W2100 2GB 1st GFX
J1Q30AV	NVIDIA Quadro K620 2GB 2nd GFX
J1Q31AV	NVIDIA Quadro K2200 4GB 2nd GFX
J1Q35AV	AMD FirePro W2100 2GB 2nd GFX
J1Q38AV	NVIDIA Quadro K2200 4GB 3rd GFX

Memory

Product #	Offering
G8X58AV	8GB DDR4-2133 (1x8GB) 1CPU RegRAM
G8X61AV	16GB DDR4-2133 (2x8GB) 1CPU RegRAM
G8X63AV	32GB DDR4-2133 (4x8GB) 1CPU RegRAM
G8X64AV	64GB DDR4-2133 (8x8GB) 1CPU RegRAM

Stable & Consistent Offerings

G8X74AV	32GB DDR4-2133 (4x8GB) 2CPU RegRAM
G8X77AV	64GB DDR4-2133 (8x8GB) 2CPU RegRAM
G8X78AV	128GB DDR4-2133 (16x8GB) 2CPU RegRAM
G8X65AV	64GB DDR4-2133 (4x16GB) 1CPU RegRAM
G8X66AV	128GB DDR4-2133 (8x16GB) 1CPU RegRAM
G8X79AV	128GB DDR4-2133 (8x16GB) 2CPU RegRAM
G8X80AV	256GB DDR4-2133 (16x16GB) 2CPU RegRAM

Optical and Removable Storage

Product #	Offering
F5G79AV	Slim SuperMulti DVDRW SATA 1st ODD
G8U90AV	Slim SuperMulti DVDRW SATA 2nd ODD

Input Devices

Product #	Offering
G8U76AV	HP USB Keyboard
G8U87AV	HP USB Optical Mouse

Technical Specifications - Processors

PROCESSORS

Xeon E5-2603 v3 1.6 1600 6C CPU	J9V77AA
Xeon E5-2609 v3 1.9 1600 6C CPU	J9V76AA
Xeon E5-2620 v3 2.4 1866 6C CPU	J9V75AA
Xeon E5-2623 v3 3.0 1866 4C CPU	J9Q18AA
Xeon E5-2630 v3 2.4 1866 8C CPU	J9Q17AA
Xeon E5-2640 v3 2.6 1866 8C CPU	J9Q16AA
Xeon E5-2637 v3 3.5 2133 4C CPU	J9Q15AA
Xeon E5-2650 v3 2.3 2133 10C CPU	J9Q14AA
Xeon E5-2660 v3 2.6 2133 10C CPU	J9Q13AA
Xeon E5-2643 v3 3.4 2133 6C CPU	J9Q12AA
Xeon E5-2670 v3 2.3 2133 12C CPU	J9Q11AA
Xeon E5-2680 v3 2.5 2133 12C CPU	J9Q10AA
Xeon E5-2683 v3 2.0 2133 14C CPU	J9Q09AA
Xeon E5-2667 v3 3.2 2133 8C CPU	J9Q08AA
Xeon E5-2690 v3 2.6 2133 12C CPU	J9Q07AA
Xeon E5-2687Wv3 3.1 2133 10C CPU	J9Q06AA
Xeon E5-2695 v3 2.3 2133 14C CPU	J9Q05AA
Xeon E5-2697 v3 2.6 2133 14C CPU	J9Q04AA
Xeon E5-2699 v3 2.3 2133 18C CPU	J9Q03AA

Technical Specifications – Storage Hard Drives

HARD DRIVES

HP SAS (Serial Attached SCSI) Hard Drives for HP Workstations

600GB SAS 15K rpm 6Gb/s 3.5" HDD

Capacity	600GB	
Height	1 in; 2.54 cm	
Width		Media Diameter 3.5 in; 8.9 cm
		Physical Size 4 in; 10.17 cm
Interface	SAS	
Synchronous Transfer Rate (Maximum)	6.0 Gb/s	
Buffer	16 MB	
Seek Time (typical reads, includes controller overhead, including settling)		Single Track 0.2 ms
		Average 3.4 ms
		Full Stroke 6.6 ms
Rotational Speed	15,000 rpm	
Logical Blocks	1,172,123,568 - 512 byte blocks	
Operating Temperature	50° to 95° F (10° to 35° C)	

300GB SAS 15K rpm 6Gb/s 3.5" HDD

Capacity	300GB	
Height	1 in; 2.54 cm	
Width		Media Diameter 3.5 in; 8.9 cm
		Physical Size 4 in; 10.17 cm
Interface	SAS	
Synchronous Transfer Rate (Maximum)	6Gb/s	
Buffer	16MB	
Seek Time (typical reads, includes controller overhead, including settling)		Single Track 0.2 ms
		Average 3.4 ms
		Full Stroke 6.6 ms
Rotational Speed	15,000 rpm	
Operating Temperature	50° to 95° F (10° to 35° C)	

600GB SAS 15K SFF HDD

Capacity	600GB	
Height	5.9 in; 15 cm	
Width		Media Diameter
Interface	12Gb/s SAS	
Synchronous Transfer Rate (Maximum)	up to 1200 MB/s (SAS single port)	
Cache	128MB	
Seek Time (typical reads, includes controller overhead, including settling)	Average	2.0ms
Rotational Speed	15K rpm	

Technical Specifications – Storage Hard Drives

	Operating Temperature	41° to 131° F (5° to 55° C)		
300GB SAS 15K SFF HDD	Capacity	300GB		
	Height	5.9 in; 15 cm		
	Width	Media Diameter	2.5 in; 6.36 cm	
	Interface	12Gb/s SAS		
	Synchronous Transfer Rate (Maximum)	up to 1200 MB/s (SAS single port)		
	Cache	128MB		
	Seek Time (typical reads, includes controller overhead, including settling)	Average	2.0ms	
	Rotational Speed	15K rpm		
	Operating Temperature	41° to 131° F (5° to 55° C)		
	HP 300GB SAS 10K SFF HDD	Capacity	300GB	
		Height	0.6 in; 1.53 cm	
Width		Media Diameter	2.5 in; 6.36 cm	
		Physical Size	2.75 in; 6.99 cm	
Interface		SAS 6Gb/s		
Synchronous Transfer Rate (Maximum)		Up to 600MB/s		
Buffer		64MB		
Cache		multi-segmentable cache buffer		
Seek Time (typical reads, includes controller overhead, including settling)		Single Track	0.4 ms (max)	
		Average	3.6 ms	
		Full Stroke	7.3 ms	
	Rotational Speed	10,000 rpm		
	Logical Blocks	585,937,500		
	Operating Temperature	41° to 131° F (5° to 55° C)		
HP 600GB SAS 10K SFF HDD	Capacity	600GB		
	Height	0.6 in; 1.53 cm		
	Width	Media Diameter	2.5 in; 6.36 cm	
		Physical Size	2.75 in; 6.99 cm	
	Interface	SAS 6Gb/s		
	Synchronous Transfer Rate (Maximum)	Up to 600MB/s		
	Buffer	64MB		
	Cache	multi-segmentable cache buffer		
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.4 ms (max)	
		Average	3.6 ms	
		Full Stroke	7.3 ms	
	Rotational Speed	10,000 rpm		

Technical Specifications – Storage Hard Drives

HP 1.2TB SAS 10K SFF HDD	Logical Blocks	1,172,123,568	
	Operating Temperature	41° to 131° F (5° to 55° C)	
	Capacity	1.2TB	
	Height	0.6 in; 1.53 cm	
	Width	Media Diameter	2.5 in; 6.36 cm
		Physical Size	2.75 in; 6.99 cm
	Interface	SAS 6Gb/s	
	Synchronous Transfer Rate (Maximum)	Up to 600MB/s	
	Buffer	64MB	
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.18ms (max)
		Average	3.5ms
		Full Stroke	7.17ms
		Rotational Speed	10,000 rpm
	Logical Blocks	2,344,225,968	
	Operating Temperature	41° to 131° F (5° to 55° C)	

SATA Hard Drives for HP Workstations	500GB SATA 10K rpm SFF HDD	Capacity	500GB		
		Height	0.6 in; 1.53 cm		
		Width	Media Diameter	2.5 in; 6.36 cm	
			Physical Size	2.75 in; 6.99 cm	
	Interface	Serial ATA (6Gb/s)			
	Synchronous Transfer Rate (Maximum)	Up to 600MB/s			
	Buffer	64MB			
	Cache	Adaptive			
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	1.2ms (typical)		
		Average	3.6ms		
		Full Stroke	9.0ms (typical)		
		Rotational Speed	10K rpm		
		Operating Temperature	41° to 131° F (5° to 55° C)		

	1TB SATA 7200 rpm 6Gb/s 3.5" HDD	Capacity	1TB		
		Height	1 in; 2.54 cm		
		Width	Media Diameter	3.5 in; 8.9 cm	
			Physical Size	4 in; 10.17 cm	
	Interface	Serial ATA (6Gb/s)			
	Synchronous Transfer Rate (Maximum)	Up to 600 MB/s			
	Buffer	64MB			
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	1.2ms (typical)		
		Average	11ms		
		Full Stroke	21ms (typical)		
		Rotational Speed	7,200 rpm		

Technical Specifications – Storage Hard Drives

	Logical Blocks	1,953,525,168	
	Operating Temperature	41° to 131° F (5° to 55° C)	
2.0TB SATA 7200 rpm 6Gb/s 3.5" HDD	Capacity	2.0TB	
	Height	1 in; 2.54 cm	
	Width	Media Diameter	3.5 in; 8.9 cm
		Physical Size	4 in; 10.17 cm
	Interface	Serial ATA (6.0 Gb/s), NCQ Enabled	
	Synchronous Transfer Rate (Maximum)	Up to 600 MB/s	
	Buffer	64MB	
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	1.0 ms
		Average	11 ms
		Full Stroke	18 ms
		Rotational Speed	7,200 rpm
		Logical Blocks	3,907,029,168
		Operating Temperature	41° to 131° F (5° to 55° C)
3.0TB SATA 7200 rpm 6Gb/s 3.5" HDD	Capacity	3.0TB	
	Height	1 in; 2.54 cm	
	Width	Media Diameter	3.5 in; 8.9 cm
		Physical Size	4.0 in; 10.17 cm
	Interface	Serial ATA (6.0Gb/s), NCQ enabled	
	Synchronous Transfer Rate (Maximum)	Up to 6.0 Gb/s	
	Buffer	64MB	
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.6 ms
		Average	11 ms
		Full Stroke	Not Specified
		Rotational Speed	7,200 rpm
		Operating Temperature	41° to 140° F (5° to 60° C)
	4TB SATA 7200 rpm 6Gb/s 3.5" HDD	Capacity	4TB
Height		1 in; 2.54 cm	
Width		Media Diameter	2.5 in; 6.36 cm
		Physical Size	2.75 in; 6.99 cm
Interface		Serial ATA (6Gb/s), NCQ enabled	
Synchronous Transfer Rate (Maximum)		Up to 600MB/s	
Buffer		128MB	
Seek Time (typical reads, includes controller overhead, including settling)		Single Track	0.7ms
		Average	8.5ms
		Full Stroke	15.7ms
		Rotational Speed	7,200 rpm

Technical Specifications – Storage Hard Drives

Operating Temperature 41° to 131° F (5° to 55° C)

500GB SATA 7.2K SED SFF HDD	Capacity	500GB
	Height	0.275 in; 0.7 cm
	Width	Media Diameter 2.5 in; 6.36 cm
		Physical Size 2.75 in; 6.99 cm
	Interface	Serial ATA (6Gb/s)
	Synchronous Transfer Rate (Maximum)	Up to 600MB/s
	Buffer	32MB
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track 1ms Average 4.2ms Full Stroke 25ms (typical)
	Rotational Speed	7,200 rpm
	Operating Temperature	32° to 140° F (0° to 60° C)

HP Solid State Drives (SSDs) for Workstations	HP 128GB SATA 6Gb/s SSD	Capacity	128GB
		Height	0.28 in; 0.7 cm
		Width	Physical Size 2.5 in; 6.36 cm
		Interface	SATA 6Gb/s
		Synchronous Transfer Rate (Maximum)	Up to 500MB/s (Sequential Read)
		Operating Temperature	32° to 158° F (0° to 70° C)

HP 256GB SATA 6Gb/s SSD	Capacity	256GB
	Height	0.28 in; 0.7 cm
	Interface	SATA 6Gb/s
	Synchronous Transfer Rate (Maximum)	Up to 500MB/s (Sequential Read)
	Operating Temperature	32° to 158° F (0° to 70° C)

HP 256GB SATA 6Gb/s SED Opal 1SSD	Capacity	256GB
	Height	0.28 in; 0.7 cm
	Width	Physical Size 2.5 in; 6.36 cm
	Interface	6Gb/s SATA
	Synchronous Transfer Rate (Maximum)	Up to 500MB/s (Sequential Read)
	Operating Temperature	32° to 158° F (0° to 70° C)

HP 512GB SATA 6Gb/s SSD	Capacity	512GB
	Height	0.28 in; 0.7 cm
	Width	Physical Size 2.5 in; 6.36 cm
	Interface	6Gb/s SATA
	Synchronous Transfer Rate (Maximum)	Up to 500MB/s (Sequential Read)

Technical Specifications – Storage Hard Drives

		Operating Temperature	32° to 158° F (0° to 70° C)
HP 1TB SATA 6Gb/s SSD	Capacity	1TB	
	Height	0.28 in; 0.7 cm	
	Width	Physical Size	2.5 in; 6.36 cm
	Interface	6Gb/s SATA	
	Synchronous Transfer Rate (Maximum)	Up to 550MB/s (Sequential Read)	
	Operating Temperature	32° to 158° F (0° to 70° C)	
Samsung Enterprise 240GB SATA SSD	Capacity	240GB	
	Width	Physical Size	2.5 in; 6.36 cm
	Interface	SATA 6Gb/s	
	Synchronous Transfer Rate (Maximum)	600 Mb/s	
Samsung Enterprise 480GB SATA SSD	Capacity	480GB	
	Width	Physical Size	2.5 in; 6.36 cm
	Interface	SATA 6Gb/s	
	Synchronous Transfer Rate (Maximum)	600 Mb/s	
Intel Pro 1500 180GB SATA SSD	Capacity	180GB	
	Width	Physical Size	2.5 in; 6.36 cm
	Interface	6Gb/s SATA	
	Synchronous Transfer Rate (Maximum)	600 Mb/s	
	Operating Temperature	32° to 158° F (0° to 70° C)	
PCIe SSDs for HP Workstations	HP Z Turbo Drive 256GB SSD	Capacity	256GB
		Interface	PCI Express 2.0 x4 electrical x4 physical
		Operating Temperature	32° to 158° F (0° to 70° C)
	HP Z Turbo Drive 512GB SSD	Capacity	512GB
		Interface	PCI Express 2.0 x4 electrical x4 physical
		Operating Temperature	32° to 158° F (0° to 70° C)
HDD Carrier	HP 4-in-1 SFF (2.5in) HDD Carrier	Dimensions (L x W x H)	6.70 x 5.75 x 1.63 in
		Kit Contents	Drive Carrier, Drive trays (4), Power adapter
		Weight	1.77 lbs

Technical Specifications - Hard Drive Controllers

LSI 9270-8i SAS 6Gb/s ROC RAID Card and iBBU9 Battery Backup Unit	PCI Bus	x8 lane PCIe 3.0 compliant
	RAID Levels	RAID 0, 1, 5, and 6 RAID spans 10, 50 and 60
	PCI Card Type	Low profile, single PCIe slot design with full height bracket.
	PCI Voltage	+3.3V Add-in Card
	PCI Power	+3.3V, +12V
	Certification Level	PCI-Express 3.0
	IO Bus	Eight 6Gb/s and 3Gb/s compatible SAS/SATA ports
	SAS Processor	LSISAS2208 Dual-Core RAID on Chip (ROC)
	Internal Connectors	Two SAS SFF8087 x4 (Mini-SAS)
	External Connectors	None
	Maximum Number of SCSI Devices	Up to 128 SAS and/or SATA hard drives and SSDs Note: HP Workstations do not support this many internal drives.
	LED Indicators	Heartbeat LED on card

Technical Specifications – Graphics

GRAPHICS

NVIDIA NVS 310 512MB Graphics

Form Factor	Low Profile: 2.7 inches (H) x 5.7 inches (L), Half-Height
Weight:	~142 grams
Graphics Controller	NVIDIA NVS 310 GPU: GF119-825
Bus Type	PCI Express x16, 2.0 compliant
Memory	Size: 512MB DDR3 Clock: 875MHz Memory Bandwidth: 14GB/s
Connectors	2 x DisplayPort
Maximum Resolution	Up to 2560 x 1600 (digital display) per display.

Image Quality Features	The following video formats are supported: <ul style="list-style-type: none">- MPEG2- MPEG4 Part 2 Advanced Simple Profile- H.264 SVC codec support- Support for 3D Blu Ray- VC1- DivX version 3.11 and later- MVC
-------------------------------	--

A full range of video resolutions are supported including 1080p, 1080i, 720p, 480p and 480i. The NVS 310 GPU provides hardware acceleration for the computationally intensive parts of video processing, as well as provides improved video playback speeds via faster decode and transcode.

Display Output	Up to 2 displays in the following configurations:
-----------------------	---

DisplayPort output:

- Drives two DisplayPort enabled digital display at resolutions up to 2560 x 1600 at 60 Hz with reduced blanking, when connected natively using the 2 DisplayPort connectors on the NVS 310 graphics card
- Supports 2 monitors up to resolution of 1920 x 1200 at 60 Hz with reduced blanking using DisplayPort 1.2 multi stream topology technology.

DVI-D output:

- Drives two digital display at resolutions up to 1920 x 1200 at 60 Hz with reduced blanking using DisplayPort to DVI-D single-link cable adaptors
- Drives two digital display at resolutions up to 2560 x 1600 at 60 Hz with reduced blanking using DisplayPort to DVI-D dual-link cable adaptors

HDMI output:

- NVS 310 is capable of driving two high definition (HD) panels up to resolutions of 1920 x 1080P at 60 Hz using DisplayPort to HDMI cable adaptors

Technical Specifications – Graphics

	VGA display output:
	<ul style="list-style-type: none"> • Drives two analog display at resolutions up to 1920 × 1200 at 60 Hz using DisplayPort to VGA cable adaptors
Shading Architecture	Shader Model 5.0
Supported Graphics APIs	DX11, OpenGL 4.1
Available Graphics Drivers	Windows 8 Genuine Windows 7 Professional (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or the latest HP qualified drivers are available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

SUSE Linux Enterprise drivers may also be obtained from:

<ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

NOTES:

1. The thermal solution used on this card is an active fan heatsink.
2. Factory configured NVS 310 graphics card have no cable adaptors included. Adapters must be ordered separately.
3. Option kit NVS 310 includes 2 DP to DVI-D cable adaptors.

NVIDIA NVS 315 512MB Graphics	Form Factor	Low Profile: 2.713 inches in height × 5.7 inches in length Weight: ~142 grams
	Graphics Controller	NVIDIA NVS 315 (using GF119-825 GPU) Number of Cores: 48 CUDA cores Max. Power: 19.3W Cooling Solution: Active fan heatsink
	Bus Type	PCI Express x16, 2.0 compliant
	Memory	Size: 1GB DDR3 Clock: 875MHz Memory Bandwidth: 14GB/s
	Connectors	DMS-59 output Cables included: - For CTO: DMS-59 to DVI cable - For AMO: DMS-59 to DVI cable and DMS-59 to VGA cable
	Maximum Resolution	Maximum number of displays supported: 2 Maximum Resolution Support: - DMS-59 to VGA: 2048 x 1536 @ 85Hz - DMS-59 to DVI: 1980 x 1200 @ 60Hz - DMS-59 to DP: 2560 x 1600 @ 60Hz
	Image Quality Features	See Display Output section. The following video formats are supported:

Technical Specifications – Graphics

- MPEG2
- MPEG4 Part 2 Advanced Simple Profile
- H.264 SVC codec support
- Support for 3D Blu Ray
- VC1
- DivX version 3.11 or later

A full range of video resolutions are supported including 1080p, 1080i, 720p, 480p and 480i. The NVS 315 GPU provides hardware acceleration for the computationally intensive parts of video processing, as well as provides improved video playback speeds via faster decode and transcode.

Display Output

Up to 2 displays using one of the following DMS-59 cables:

- DMS-59 to DVI
- DMS-59 to VGA
- DMS-59 to DP

DisplayPort output:

- Drives two DisplayPort enabled digital displays at resolutions up to 2560 × 1600 at 60 Hz with reduced blanking, when connected via the DMS-59 to DP adaptor.

DVI-D output:

- Drives two digital displays at resolutions up to 1920 × 1200 at 60 Hz with reduced blanking using DMS-59 to DVI-D single-link cable adaptor

VGA display output:

- Drives two analog displays at resolutions up to 2048 × 1536 at 85 Hz using DMS-59 to VGA cable adaptor.

Shading Architecture

Shader Model 5.0

Supported Graphics APIs

DX11, OpenGL 4.3

Available Graphics Drivers

Windows 8
Microsoft Windows 7 Professional (64-bit and 32-bit)
Microsoft Windows XP Professional (64-bit and 32-bit)
Red Hat Enterprise Linux(RHEL)
SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or the latest HP qualified drivers are available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

SUSE Linux Enterprise drivers may also be obtained from:

<ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

NOTES:

1. The thermal solution used on this card is an active fan heatsink.
2. Factory configured graphics card includes DMS-59 to DVI cable.
3. Option kit graphics card includes DMS-59 to DVI and DMS-59 to VGA cables (one each).

Technical Specifications – Graphics

NVIDIA NVS 510 2GB Graphics	Form Factor	Low Profile, 2.713 inches × 6.3 inches, single slot
	Graphics Controller	NVS 510 GPU Core Clock: 797 MHz Memory Clock: 891 MHz CUDA Cores: 192
	Bus Type	PCI Express x16, Generation 2.0
	Memory	2GB DDR3
	Connectors	Four mini-DisplayPort. Four mini-DisplayPort to DisplayPort adapters included. (DisplayPort to DVI-D, DisplayPort to VGA, DisplayPort to HDMI, and DisplayPort to Dual-Link DVI adapters available as separate accessories)
	Maximum Resolution	Mini-DisplayPort connectors support ultra-high-resolution panels (up to 3840 x 2160 @ 60Hz)
	Image Quality Features	NOTE: This card supports up to four displays. For Windows XP, only 2 active displays are supported. 10-bit internal display processing, including hardware support for 10-bit scan-out
	Display Output	<p>DisplayPort with Multi-Stream Technology (MST) and High Bit Rate 2 (HBR2) support.</p> <p>Digital Display Support</p> <p>1. DisplayPort Output</p> <ul style="list-style-type: none"> • Drives four DisplayPort enabled digital display at resolutions up to 3840 × 2160 at 60 Hz with reduced blanking, when connected natively using the 4 DisplayPort connectors on the NVS 510 graphics card. • DisplayPort Multi-Stream Topology (MST) Technology: Supports various combinations of display resolutions and number of displays when using DisplayPort multi stream topology technology – up to a maximum of 4 monitors at a resolution of 1920 × 1200 at 60 Hz with reduced blanking. <p>2. DVI-D Output</p> <ul style="list-style-type: none"> • Drives four digital displays at resolutions up to 1920 × 1200 at 60 Hz with reduced blanking using DisplayPort to DVI-D single-link cable adaptors. • Drives four digital displays at resolutions up to 2560× 1600 at 60 Hz with reduced blanking using DisplayPort to DVI-D dual-link cable adaptors. <p>HDMI Output</p> <ul style="list-style-type: none"> • The NVS 510 graphics board is capable of driving four high definition (HD) panels up to resolutions of 1920 × 1080P at 60 Hz using DisplayPort to HDMI cable adaptors. <p>Analog Display Support</p> <p>1. VGA display output</p> <ul style="list-style-type: none"> • Drives four analog displays at resolutions up to 1920 × 1200 at 60 Hz using DisplayPort to VGA cable adaptors.

Technical Specifications – Graphics

Supported Graphics APIs	Full Microsoft DirectX 11, Shader Model 5.0 support Full OpenGL 4.3 support
Available Graphics Drivers	Genuine Windows 7 Professional (64-bit and 32-bit) Microsoft Windows XP Professional (64-bit and 32-bit) Red Hat Enterprise Linux(RHEL) 6 Desktop/Workstation SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)
	HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html

NOTE: Heatsink cooler design is active.

Graphics Cable Adapters

Graphics Cable Adapter option choice is available starting Feb 1 2013 for the following graphics cards:
NVS 310, Quadro 410, Quadro K5000, FirePro V3900, FirePro W7000

New Graphics Cards introduced after Feb 1 2013 will be eligible for choosing Graphics Cable Adapters, unless otherwise specified.

No cable choice for NVS 300, NVS 510.

Maximum number of cables allowed is 8.

NVIDIA Quadro K420 1GB Graphics	Form Factor	Low Profile: 2.713 inches × 6.3 inches, single slot
	Graphics Controller	NVIDIA Quadro K420 GPU: GK107
	Bus Type	PCI Express x16, 2.0 compliant
	Memory	Size: 1GB DDR3 Clock: 891MHz Memory Bandwidth: 29GB/s
	Connectors	One dual-link DVI-I connector One DisplayPort connector
	Maximum Resolution	VGA (via adapter cable): <ul style="list-style-type: none"> 2048 × 1536 × 32 bpp at 85 Hz Dual-link DVI <ul style="list-style-type: none"> 2560 × 1600 × 32 bpp at 60 Hz (reduced blanking) Single-link DVI <ul style="list-style-type: none"> 920 × 1200 × 32 bpp at 60 Hz (reduced blanking) DisplayPort 1.2 <ul style="list-style-type: none"> 3840 × 2160 × 30 bpp at 60 Hz
	RAMDAC	400 MHz integrated RAMDAC
	Display Output	Maximum number of displays supported: 2
	Shading Architecture	Shader Model 5.0
	Supported Graphics APIs	DX11, OpenGL 4.4

Technical Specifications – Graphics

Programming support for CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Python, and Fortran

Available Graphics Drivers

Microsoft Windows 8.1
Microsoft Windows 8
Microsoft Windows 7
Linux

1. Factory configured Quadro K420 does not include any video adapters. Adapters must be ordered separately.
2. Option kit Quadro K420 includes one DP to DVI-D adapter.

NVIDIA Quadro K620 2GB Graphics Form Factor

2.713" H x 6.3" L
Single Slot, Low Profile
Full Height Profile bracket installed
Low Profile bracket included
Weight: 133 grams

Graphics Controller

NVIDIA Quadro K620 Graphics Card
GM107 GPU
384 CUDA cores
Max Power: 45 Watts

Bus Type

PCI Express 2.0 x16

Memory

2 GB GDDR3, 900 MHz
128-bit memory I/O path
29 GB/s memory bandwidth

Connectors

1 DL-DVI(I) output, 1 DisplayPort output
Factory Configured: No video cable adapter included
Option Kit: One DP-to-DVI adapter included with card

Additional DVI-to-VGA, DisplayPort-to-VGA or DisplayPort-to-DVI adapters are available as Factory Configuration or Option Kit accessories.

Maximum Resolution

DisplayPort 1.2:
- up to 4096x2160 x 30 bpp @ 60Hz
- supports High Bit Rate 2 (HBR2) and Multi-Stream Transport (MST)

Dual Link DVI(I) output:
- up to 2560 x 1600 x 32 bpp @ 60Hz

Single Link-DVI(I) output:
- up to 1920 x 1200 x 32 bpp @ 60Hz

Image Quality Features

10-bit internal display processing pipeline
10-bit scan-out support

Display Output

1 Dual-link DVI-I connector
1 Display Port connector

Shading Architecture

Full Microsoft DirectX 11.1 Shader Model 5.0

Supported Graphics APIs

OpenGL 4.4
DirectX 11.1
API support includes:
CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran

Available Graphics Drivers

Microsoft Windows 8.1
Microsoft Windows 8
Microsoft Windows 7

Technical Specifications – Graphics

Linux

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

1. Factory configured Quadro K620 does not include a video cable adapter. Video cable adapters must be ordered separately.
2. Quadro K620 offered as an Option Kit (AMO) includes one DP-to-DVI video cable adapter. Additional cables must be ordered separately.

AMD FirePro W2100 2GB Graphics	Form Factor	Low Profile, half length (full-height bracket included)
	Graphics Controller	AMD FirePro™ W2100 professional graphics based on Oland GPU. GPU: 320 Stream Processors organized into 5 Compute Units GPU Frequency: 630MHz Power: 35W Cooling: Active
	Bus Type	PCI Express® x8, Generation 3.0
	Memory	2GB DDR3 memory Memory Bandwidth: 28.8 GB/s Memory Width: 128bit
	Connectors	2x Display Port 1.2 connectors Factory Configured: No video cable adapter included Option Kit: One DP-to-DVI adapter included with card Additional DisplayPort-to-VGA or DisplayPort-to-DVI adapters are available as Factory Configuration or Option Kit accessories.
	Maximum Resolution	DisplayPort 1.2: up to 4096x2160 x 30 bpp @ 60Hz Dual Link DVI(I) (requires adapter cable): up to 2560 x 1600 x 32 bpp @ 60Hz Single Link-DVI(I)(requires adapter): up to 1920 x 1200 x 32 bpp @ 60Hz VGA(requires adapter): up to 1920 x 1200 x 32 bpp @ 60Hz
	Image Quality Features	Advanced support for 8-bit, 10-bit, and 16-bit per RGB color component. High bandwidth scaler for high quality up and downscaling.
	Display Output	2 x DisplayPort® 1.2 Maximum number of displays: 2
	Shading Architecture	Shader Model 5.0
	Supported Graphics APIs	OpenCL™ 2.0, DirectX® 11.2/12 and OpenGL 4.4
	Available Graphics Drivers	Windows 8.1 (64-bit and 32-bit) Windows 7 (64-bit and 32-bit) Linux

Technical Specifications – Graphics

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

NOTE: Depending on the card model, native DisplayPort™ connectors and/or certified DisplayPort™ active or passive adapters to convert your monitor's native input to your card's DisplayPort™ or Mini-DisplayPort™ connector(s) may be required. See <http://www.amd.com/firepro> for details

AMD FirePro W5100 4GB Graphics	Form Factor	Full height, single slot (6.75" X 4.376")
	Graphics Controller	AMD FirePro W5100 graphics GPU Frequency: 930Mhz GPU: 768 Stream Processors organized into 12 Compute Units Power: <75 Watts Cooling: Active
	Bus Type	PCI Express® x16, Generation 3.0
	Memory	4GB GDDR5 memory Memory Bandwidth: up to 96 GB/s Memory Width: 128 bit
	Connectors	4x Display Port 1.2 connectors with HBR2 and MST support. Factory Configured: No video cable adapter included After market option kit: No video cable adapter included Additional DisplayPort-to-VGA or DisplayPort-to-DVI adapters are available as Factory Configuration or Option Kit accessories.
	Maximum Resolution	DisplayPort: - 4096x2160 @24bpp 60Hz Dual Link DVI: - 2560x1600 (requires DP to DL-DVI adapter) Single Link DVI: - 1920x1200 (requires DP to DVI adapter) VGA: - 1920x1200 (requires DP to VGA adapter)
	Image Quality Features	Advanced support for 8-bit, 10-bit, and 16-bit per RGB color component. High bandwidth scaler for high quality up and downscaling
	Display Output	Max number of monitors supported using DisplayPort 1.2a: - 4 direct attached monitors - 6 using DP 1.2a with MST and HBR2 enabled monitors Monitor chaining from a single DisplayPort (subject to a max of 6 total monitors across all outputs, requires use of DisplayPort enabled monitors supporting MST and HBR2): - one 4096x2160 display

Technical Specifications – Graphics

- two 2560x1600 displays
- four 1920x1200 displays

Shading Architecture Shader Model 5.0

Supported Graphics APIs OpenGL 4.4
OpenCL 1.2 and 2.0
DirectX 11.2 / 12
AMD Mantle

Available Graphics Drivers Windows 8.1 / 8 (64-bit and 32-bit)
Windows® 7 (64-bit and 32-bit)
Linux

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

Notes 1. AMD Eyefinity technology supports up to six DisplayPort™ monitors on an enabled graphics card. Supported display quantity, type and resolution vary by model and board design; confirm specifications with manufacturer before purchase. To enable more than two displays, or multiple displays from a single output, additional hardware such as DisplayPort-ready monitors or DisplayPort 1.2 MST-enabled hubs may be required. A maximum of two active adapters is recommended for consumer systems. See www.amd.com/eyefinityfaq for full details.

NVIDIA Quadro K2200 2GB Graphics

Form Factor 4.38" H x 7.97" L
Single Slot, Full Height

Weight: 240 grams

Graphics Controller NVIDIA Quadro K2200 Graphics Card
GM107 GPU
640 CUDA cores
Max Power: 67.7 Watts

Bus Type PCI Express 2.0 x16

Memory 4 GB GDDR5, 2500 MHz
128-bit memory I/O path
80 GB/s memory bandwidth

Connectors 1 DL-DVI(I) output, 2 DisplayPort outputs
Factory Configured Option: No video cable adapter included
Option Kit: One DP-to-DVI adapter included with card

Additional DVI-to-VGA, DisplayPort-to-VGA or DisplayPort-to-DVI adapters are available as accessories

Maximum Resolution DisplayPort:
- up to 4096 x 2160 x 30 bpp @ 60Hz
- supports High Bit Rate 2 (HBR2) and Multi-Stream Transport (MST)

DL-DVI(I) output:
- up to 2560 x 1600 x 32 bpp @ 60Hz

Single Link-DVI(I) output:
- up to 1920 x 1200 x 32 bpp @ 60Hz

Technical Specifications – Graphics

	VGA (via adapter cable): - 2048 × 1536 × 32 bpp at 85 Hz
Image Quality Features	12-bit internal display pipeline (hardware support for 12-bit scan-out on supported panels, applications and connection) Stereoscopic 3D display support including NVIDIA® 3D Vision™ technology, 3D DLP, Interleaved, and passive stereo
Display Output	Maximum number of displays - 3 direct attached monitors - 4 using DP 1.2a with MST and HBR2 enabled monitors Maximum number of DisplayPort displays possible (may require MST and/or HBR2): - 4 1920x1200 - 4 2560x1600 - 2 4096x2160 Maximum number of monitors across all available Quadro K2200 outputs is 4.
Shading Architecture	Full Microsoft DirectX 11.1 Shader Model 5.0
Supported Graphics APIs	OpenGL 4.4 DirectX 11.1 API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
Available Graphics Drivers	Microsoft Windows 8.1 Microsoft Windows 8 Microsoft Windows 7 Linux HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html <ol style="list-style-type: none"> 1. Quadro K2200 offered as Factory Configured Option does not include a video cable adapter. Video cable adapters must be ordered separately. 2. Quadro K2200 offered as an Option Kit includes one DP-to-DVI video cable adapter. Additional cables must be ordered separately. 3. A total maximum of 4 active monitors are supported across all display output types. This may be accomplished by using daisy chained DisplayPort 1.2 displays or a DisplayPort 1.2 hub device. 4. A DisplayPort hub device may be used to connect multiple DisplayPort monitors to a single Quadro K2200 DisplayPort output.

NVIDIA Quadro K4200 4GB Form Factor Graphics

4.376" H x 9.5" L
Single Slot, Full Height
Weight: ~461 grams (without extender)

Technical Specifications – Graphics

Graphics Controller	NVIDIA Quadro K4200 Graphics Card Kepler GK104 GPU 1344 CUDA cores Max Power: 108 Watts
Bus Type	PCI Express 2.0 x16
Memory	4 GB GDDR5, 2700 MHz 256-bit memory I/O path 173 GB/s memory bandwidth
Connectors	1 DL-DVI(I) 2 DisplayPort 1.2a CTO: No video cable adapter included AMO: One DP-to-DVI adapter included with card
Maximum Resolution	Additional DVI-to-VGA, DisplayPort-to-VGA or DisplayPort-to-DVI adapters are available as accessories DisplayPort: - up to 3840 x 2160 x 30 bpp @ 60Hz - supports High Bit Rate 2 (HBR2) and Multi-Stream Transport (MST) DL-DVI(I) output: - up to 2560 x 1600 x 32 bpp @ 60Hz Single Link-DVI(I) output: - up to 1920 x 1200 x 32 bpp @ 60Hz VGA (via adapter cable): - 2048 x 1536 x 32 bpp at 85 Hz
Image Quality Features	10-bit internal display processing (hardware support for 10-bit scanout for both windowed desktop and full screen, only available on Windows with Aero disabled and Linux) NVIDIA® 3D Vision™ technology, 3D DLP, Interleaved, and other 3D stereo format support Full OpenGL quad buffered stereo support Support for large-scale, ultra-high resolution visualization using the NVIDIA® SVS platform which includes NVIDIA® Mosaic, NVIDIA® Sync and NVIDIA® Warp/Blend technologies
Display Output	Maximum number of displays - 3 direct attached monitors - 4 using DP 1.2a with MST and HBR2 enabled monitors Maximum number of DisplayPort displays possible (may require MST and/or HBR2): - 4 1920x1200 - 4 2560x1600 - 2 3840x2160 Maximum number of monitors across all available Quadro K4200 outputs is 4.

Technical Specifications – Graphics

Shading Architecture	Shader Model 5.0
Supported Graphics APIs	OpenGL 4.4 DirectX 11.1 API support includes: CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
Available Graphics Drivers	Microsoft Windows 8.1 Microsoft Windows 8 Microsoft Windows 7 Linux

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

NOTES:

Quadro K4200 offered as CTO does not include a video cable adapter. Video cable adapters must be ordered separately.
Quadro K4200 offered as AMO includes one DP-to-DVI video cable adapter. Additional cables must be ordered separately.
A total maximum of 4 active monitors are supported across all display output types. This may be accomplished by using daisy chained DisplayPort 1.2 displays or a DisplayPort 1.2 hub device.
A DisplayPort hub device may be used to connect multiple DisplayPort monitors to a single Quadro K4200 DisplayPort output.

NVIDIA Quadro K5200 8GB Graphics Dimensions

4.376" H x 10.5" L
Dual Slot

Weight: ~880 grams (without extender)

Graphics Controller NVIDIA Quadro K5200
GPU: GK110-850-B1 with 2304 CUDA cores
Power: 150 Watts

Bus Type PCI Express 3.0 x16

Memory Size: 8GB GDDR5
Memory bandwidth: 192GB/s
Memory Width: 256-bit

Connectors DVI-I (1), DVI-D (1), DP (2), Optional 3D Stereo bracket with 3-pin mini-DIN connector.

Factory configured option: No adapter included with card.
Option Kit: No adaptor included with card.

DVI to VGA, DisplayPort to VGA, DisplayPort to DVI, and DisplayPort to Dual-Link DVI adapters available as accessories.

Maximum Resolution DisplayPort:
- up to 4096 x 2160 x 30 bpp @ 60Hz
- supports High Bit Rate 2 (HBR2) and Multi-Stream Transport (MST)

DL-DVI(I) output:

Technical Specifications – Graphics

- up to 2560 x 1600 x 32 bpp @ 60Hz

Single Link-DVI(I) output:

- up to 1920 x 1200 x 32 bpp @ 60Hz

VGA (via adapter cable):

- 2048 x 1536 x 32 bpp at 85 Hz

Image Quality Features

10-bit internal display processing (hardware support for 10-bit scanout for both windowed desktop and full screen, only available on Windows with Aero disabled and Linux).

NVIDIA® 3D Vision™ technology, 3D DLP, Interleaved, and other 3D stereo format support.

Full OpenGL quad buffered stereo support.

Support for NVIDIA® Quadro® Mosaic, NVIDIA® nView® multi-display technology, NVIDIA® Enterprise Management Tools.

Support for large-scale, ultra-high resolution visualization using the NVIDIA® SVS platform which includes NVIDIA® Mosaic, NVIDIA® Sync and NVIDIA® Warp/Blend technologies.

Display Output

Maximum number of displays

- 4 direct attached monitors
- 4 using DP 1.2a with MST and HBR2 enabled monitors

Maximum number of DisplayPort displays possible (may require MST and/or HBR2):

- 4 1920x1200
- 4 2560x1600
- 2 4096x2160

Maximum number of monitors across all available Quadro K5200 outputs is 4.

Shading Architecture

Shader Model 5.0

Supported Graphics APIs

OpenGL 4.4
DirectX 11

API support for NVIDIA's CUDA™ C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, Fortran

Available Graphics Drivers

Windows 8.1
Windows 8
Windows 7
Linux - Full OpenGL implementation, complete with NVIDIA and ARB extensions

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

Technical Specifications – Graphics

NOTES:

1. Factory configured Quadro K5200 does not include a video cable adapter. Video cable adapters must be ordered separately.
2. A total maximum of 4 active monitors are supported across all display output types. This may be accomplished by using daisy chained DisplayPort 1.2 displays (displays must support MST and HBR2).

NVIDIA Quadro K6000 12GB Graphics	Form Factor	4.376" H x 10.5" L Dual Slot Power: 234 Watts
	Weight:	~880 grams
	Graphics Controller	NVIDIA Quadro K6000 Graphics Card based on the GK180 GPU Core Count: 2880 Base Clock: 797 MHz Boost Clock: 902 MHz
	Bus Type	PCI Express 3.0 x16
	Memory	12GB GDDR5 384-bit memory I/O path 288 GB/s memory bandwidth ECC Memory
	Connectors	DVI-I (1), DVI-D (1), DP (2), Optional 3D Stereo bracket with 3-pin mini-DIN connector. Factory configured option: No adapter included with card. Option Kit: No adaptor included with card. DVI to VGA, DisplayPort to VGA, DisplayPort to DVI, and DisplayPort to Dual-Link DVI adapters available as accessories.
	Image Quality Features	<ul style="list-style-type: none"> • DisplayPort with Multi-Stream Technology (MST) and High Bit Rate 2 (HBR2), HDMI 1.4, and HDCP support • NVIDIA 3D Vision™ technology • NVIDIA Premium Mosaic and nView
	Display Output	400 MHz integrated RAMDAC <ul style="list-style-type: none"> • Maximum resolution over VGA (through DVI to VGA cable): 2048 × 1536 × 32 bpp at 85 Hz Dual-link internal TMDS (DVI 1.0) <ul style="list-style-type: none"> • Maximum resolution over digital port (single GPU and SLI mode): 2560 × 1600 × 32 bpp at 60 Hz (reduced blanking) Single-link internal TMDS (DVI 1.0) <ul style="list-style-type: none"> • Maximum resolution over digital port (single GPU and SLI mode): 1920 × 1200 × 32 bpp at 60 Hz (reduced blanking)

Technical Specifications – Graphics

DisplayPort with MST and HBR2.

- Maximum resolution: 3840 × 2160 × 36 bpp at 60Hz

HDMI

- Maximum resolution: 1920 × 1080 × 32 bpp at 60Hz

Shading Architecture

Shader Model 5.0
Full IEEE 764-2008 32-bit and 64-bit precision

Supported Graphics APIs

Full OpenGL 4.3
Full DirectX 11
CUDA API support includes:
CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran

Available Graphics Drivers

Windows 8
Windows 7 Professional (64-bit and 32-bit)
Red Hat Enterprise Linux (RHEL) 6 Desktop/Workstation
SUSE Linux Enterprise Desktop 11 (64-bit and 32-bit)

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

Novell SUSE Linux Enterprise drivers may also be obtained from:

<ftp://download.nvidia.com/novell> or <http://www.nvidia.com>

NOTES:

NVIDIA GRID VGX Pass Through feature supported on NVIDIA Quadro K6000 to enable direct mapping of GPU to Virtual Machine.
No display output adapter included.

AMD FirePro W7100 8GB Graphics

Form Factor

Full height, single slot (9.5" X 4.376")

Graphics Controller

AMD FirePro W7100 graphics
GPU: 1792 Stream Processors organized into 28 Compute Units
Power: <75 Watts
Cooling: Active

Bus Type

PCI Express® x16, Generation 3.0

Memory

8GB GDDR5 memory
Memory Bandwidth: up to 176 GB/s
Memory Width: 256 bit

Connectors

4x Display Port 1.2a connectors with HBR2 and MST support.

Factory Configured: No video cable adapter included
After market option kit: No video cable adapter included

Technical Specifications – Graphics

Additional DisplayPort-to-VGA or DisplayPort-to-DVI adapters are available as Factory Configuration or Option Kit accessories.

Maximum Resolution

DisplayPort:
- 4096x2160 @24bpp 60Hz

Dual Link DVI:
- 2560x1600 (requires DP to DL-DVI adapter)

Single Link DVI:
- 1920x1200 (requires DP to DVI adapter)

VGA:
- 1920x1200 (requires DP to VGA adapter)

Image Quality Features

Advanced support for 8-bit, 10-bit, and 16-bit per RGB color component. High bandwidth scaler for high quality up and downscaling

Display Output

Max number of monitors supported using DisplayPort 1.2a:
- 4 direct attached monitors
- 6 using DP 1.2a with MST and HBR2 enabled monitors

Monitor chaining from a single DisplayPort (subject to a max of 6 total monitors across all outputs, requires use of DisplayPort enabled monitors supporting MST and HBR2):
- one 4096x2160 display
- two 2560x1600 displays
- four 1920x1200 displays

Shading Architecture

Shader Model 5.0

Supported Graphics APIs

OpenGL 4.4
OpenCL 1.2 and 2.0
DirectX 11.2 / 12
AMD Mantle

Available Graphics Drivers

Windows 8.1 / 8 (64-bit and 32-bit)
Windows® 7 (64-bit and 32-bit)
Linux

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://welcome.hp.com/country/us/en/support.html>

Notes

1. AMD Eyefinity technology supports up to six DisplayPort™ monitors on an enabled graphics card. Supported display quantity, type and resolution vary by model and board design; confirm specifications with manufacturer before purchase. To enable more than two displays, or multiple displays from a single output, additional hardware such as DisplayPort-ready monitors or DisplayPort 1.2 MST-enabled hubs may be required. See www.amd.com/eyefinityfaq for full details.
2. OpenGL 4.4 support available with driver 14.301.xxx or later.
3. OpenCL 2.0 support planned in driver updates for early 2015.
4. For HP Z440 Workstation configurations, the HP Z4 Fan and Front Card

Technical Specifications – Graphics

Guide Kit, which is available both CTO (G8T99AV) and AMO (J9P80AA), is required.

NVIDIA Quadro M6000 12GB Graphics	Form Factor	4.42" H x 10.5" L Dual Slot Power: 250 Watts Weight: ~1030 grams
	Graphics Controller	NVIDIA Quadro M6000 Graphics Card based on the GM200 GPU Core Count: 3072 Base Clock: 1026 MHz Boost Clock: 1152 MHz Idle Clock: 324 MHz
	Bus Type	PCI Express 3.0 x16
	Memory	12GB GDDR5 384-bit memory I/O path 317 GB/s memory bandwidth ECC Memory (disabled by default)
	Connectors	DP (x4) DL-DVI(I) 3-pin mini-DIN connector SLI connector Quadro Sync connector One 8-pin auxiliary power connector Factory configured option: No adapter included with card. Option Kit: No adaptor included with card. DVI to VGA, DisplayPort to VGA, DisplayPort to DVI, and DisplayPort to Dual-Link DVI adapters available as accessories.
	Image Quality Features	<ul style="list-style-type: none"> • DisplayPort with Multi-Stream Technology (MST) and High Bit Rate 2 (HBR2), HDMI 1.4, and HDCP 1.3 support • NVIDIA 3D Vision™ technology • NVIDIA Premium Mosaic and nView
	Display Output	400 MHz integrated RAMDAC <ul style="list-style-type: none"> • Maximum resolution over VGA (through DVI to VGA cable): 2048 × 1536 × 32 bpp at 85 Hz Dual-link internal TMDS (DVI 1.0) <ul style="list-style-type: none"> • Maximum resolution over digital port (single GPU and SLI mode): 2560 × 1600 × 32 bpp at 60 Hz (reduced blanking) Single-link internal TMDS (DVI 1.0) <ul style="list-style-type: none"> • Maximum resolution over digital port (single GPU and SLI mode): 1920 × 1200 × 32 bpp at 60 Hz (reduced blanking) DisplayPort 1.2 with MST and HBR2. <ul style="list-style-type: none"> • Maximum pixel clock: 592 MPixel/s

Technical Specifications – Graphics

- Maximum bandwidth: 17.2 Gbps
- Example maximum resolution: 4096 × 2160 × 30 bpp at 60Hz

HDMI

- Maximum resolution: 4096 × 2160 × 8 bpp at 60Hz

Shading Architecture Shader Model 5.0

Supported Graphics APIs Full OpenGL 4.4
Full DirectX 12
API support includes:
CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran

Available Graphics Drivers Windows 8.1
Windows 8
Windows 7 Professional
Linux

HP qualified drivers may be preloaded or available from the HP support Web site:

<http://www8.hp.com/us/en/drivers.html>

Notes

1. NVIDIA GRID VGX Pass Through feature supported on NVIDIA Quadro M6000 to enable direct mapping of GPU to Virtual Machine.
2. No display output adapter included.
3. For HP Z840 Workstation configurations, the 1125W power supply option must be used.

Technical Specifications – High Performance GPU Computing

HIGH PERFORMANCE GPU COMPUTING

NVIDIA Tesla K40 Workstation Compute Processor	Form Factor	Size: 4.376 inches by 10.5 inches Slots: Dual Slot Power Connectors: One 6-pin and one 8-pin Weight: ~826 grams
	System Interface	PCI Express Gen3 ×16
	Video Outputs	None.
	Memory	12GB GDDR5, memory path: 384-bit memory clock: 3Ghz
	Peak Memory Bandwidth	288 GB/s
	Supported APIs	CUDA, OpenACC, OpenCL 1.2 API support includes: C, C++, Java, Python, and Fortran
	Supported Operating Systems	Windows 8 (64-bit) Genuine Windows 7 Professional (64-bit) Red Hat Enterprise Linux (RHEL) 5, 6 Desktop/Workstation (64-bit) SUSE Linux Enterprise Desktop 11 (64-bit) HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/en/support.html Novell SUSE Linux Enterprise drivers may also be obtained from: ftp://download.nvidia.com/novell or http://www.nvidia.com
	Processor Cores	GK110B GPU Base Clock: 745 MHz Boost Clock: up to 875 Mhz 2888 CUDA cores
	Power Consumption	~235 Watts

Note 1: A 1125W PSU is required for any K40 configuration on the Z820

Technical Specifications - Optical and Removable Storage

OPTICAL AND REMOVABLE STORAGE

HP 9.5mm Slim SuperMulti DVD Writer

Description	9.5mm height, tray-load	
Mounting Orientation	Either horizontal or vertical	
Interface Type	SATA/ATAPI	
Dimensions (WxHxD)	128 x 9.5 x 127mm	
Supported Media Types	DVD-RAM DVD+R DVD+RW DVD+R DL DVD-R DL DVD-R DVD-RW CD-R CD-RW	
Disc Capacity	DVD-ROM	8.5 GB DL or 4.7 GB standard
	Full Stroke DVD	< 200 ms (seek)
	Full Stroke CD	< 200 ms (seek)
Maximum Data Transfer Rates	CD ROM Read	CD-ROM, CD-R Up to 24X CD-RW Up to 24X
	DVD ROM Read	DVD-RAM Up to 8X DVD+RW Up to 8X DVD-RW Up to 8X DVD+R DL Up to 8X DVD-R DL Up to 8X DVD-ROM Up to 8X DVD-ROM DL Up to 8X DVD+R Up to 8X DVD-R Up to 8X
Power	Source	SATA DC power receptacle
	DC Power Requirements	5 VDC ± 5%-100 mV ripple p-p
	DC Current	5 VDC -< 800 mA typical, <1600 mA maximum
Operating Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative Humidity	10% to 80%
	Maximum Wet Bulb Temperature	84° F (29° C)
Operating Systems Supported	Windows 8.1, Windows 8 32-bit and 64-bit, Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation SUSE Linux Enterprise Desktop 10 & 11	

No driver is required for this device. Native support is provided by the operating system.

Technical Specifications - Optical and Removable Storage

Kit Contents	9.5mm Slim SuperMulti DVD Writer, 5.25" ODD Bay adapter/carrier, slim SATA data/power cable, installation guide
---------------------	---

HP 9.5mm Slim DVD-ROM Drive	Description	9.5mm height, tray-load	
	Mounting Orientation	Either horizontal or vertical	
	Interface Type	SATA / ATAPI	
	Dimensions (WxHxD)	128 x 9.5 x 127mm	
	Disc Capacity	DVD-ROM Single layer: Up to 4.7 GB Double layer: Up to 8.5 GB	
	Access Times	DVD-ROM Single Layer	< 110 ms (typical)
		CD-ROM Mode 1	< 110 ms (typical)
		Full Stroke DVD	< 230 ms (typical)
		Full Stroke CD	< 220 ms (typical)
	Power	Source	SATA DC power receptacle
		DC Power Requirements	5 VDC ± 5%-100 mV ripple p-p
		DC Current	5 VDC – <800mA typical, < 1600 mA maximum
	Operating Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
Relative Humidity		10% to 80%	
Maximum Wet Bulb Temperature		84° F (29° C)	
Operating Systems Supported	Windows 8.1, Windows 8 32-bit and 64-bit, Windows 7 Professional 32-bit and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*. Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation SUSE Linux Enterprise Desktop 10 & 11		
	No driver is required for this device. Native support is provided by the operating system.		
Kit Contents	9.5mm Slim DVD-ROM Drive, 5.25" ODD Bay adapter/carrier, slim SATA data/power cable, installation guide		

HP 9.5mm Slim BDXL Blu-Ray Writer	Description	9.5mm height, tray-load
	Mounting Orientation	Either horizontal or vertical
	Interface Type	SATA/ATAPI
	Dimensions (WxHxD)	128 x 9.5 x 127mm
	Supported Media Types	BD-ROM BD-R BD-RE DVD-RAM DVD+R DVD+RW DVD+R DL DVD-R DL

Technical Specifications - Optical and Removable Storage

	DVD-R DVD-RW CD-R CD-RW	
Disc Capacity	DVD-ROM Blu-ray	8.5 GB DL or 4.7 GB standard 25 GB (single-layer) 50 GB (dual-layer) 100/128 GB (BDXL)
	Full Stroke DVD Full Stroke CD Blu-ray Startup Time	< 230 ms (seek) < 220 ms (seek) < 230 ms (seek) (Full Stroke Blu-ray) (Time to drive ready from tray loading)
		BD-ROM (SL/DL) 25S / 28S BD-R (SL/DL) 25S / 28S BD-RE (SL/DL) 25S / 28S DVD-ROM (SL/DL) 18S / 18S DVD-R (SL/DL) 25S / 25S DVD-RW 25S DVD+R (SL/DL) 25S / 25S DVD+RW 25S DVD-RAM 45S CD-ROM 15S
Maximum Data Transfer Rates	CD ROM Read DVD ROM Read Blu-ray	CD-ROM, CD-R Up to 24X CD-RW Up to 24X DVD-RAM Up to 8X DVD+RW Up to 8X DVD-RW Up to 8X DVD+R DL Up to 8X DVD-R DL Up to 8X DVD-ROM Up to 8X DVD-ROM DL Up to 8X DVD+R Up to 8X DVD-R Up to 8X BD-ROM Up to 6X BD-ROM DL Up to 6X BD-R Up to 6X BD-R DL Up to 6X BD-R Up to 6X BD-RE SL/DL Up to 6X
Power	Source DC Power Requirements DC Current	SATA DC power receptacle 5 VDC ± 5%-100 mV ripple p-p 5 VDC -900 mA typical, 2000mA maximum
Operating Environmental (all conditions non-condensing)	Temperature Relative Humidity Maximum Wet Bulb Temperature	41° to 122° F (5° to 50° C) 10% to 80% 84° F (29° C)
Operating Systems	Windows 8.1, Windows 8 32-bit and 64-bit, Windows 7 Professional 32-bit	

Technical Specifications - Optical and Removable Storage

Supported and 64-bit, Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows 2000, Windows XP Professional or Windows XP Home 32*.
Red Hat Enterprise Linux(RHEL) WS4**, 5, 6 Desktop/Workstation
SUSE Linux Enterprise Desktop 10 & 11

No driver is required for this device. Native support is provided by the operating system.

Kit Contents 9.5mm Slim BDXL Blu-Ray Writer, 5.25" ODD Bay adapter/carrier, slim SATA data/power cable, installation guide
As Blu-ray is a new format containing new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD-DVD movies cannot be played on this workstation.

HP DX115 Removable Drive Enclosure

Interface Type Compatible with SAS or SATA controllers. Offers 6Gb/s performance when used with 6Gb/s HDDs.

Dimensions (WxHxD) 147.6 x 41.1 x 205 mm (5.81 x 1.62 x 8.08 in)

Weight Frame and Carrier: 1.73 kg (3.8 lbs.)
Carrier: 0.45 kg (1 lbs.)

HP 15-in-1 Media Card Reader

Description Supports hardware ECC (Error Correction Code) function
Supports hardware CRC (Cyclic Redundancy Check) function
Supports MS 4-bit parallel transfer mode
Supports MS-PRO 4-bit parallel transfer mode
Supports MS PRO-HG Duo 4-bit parallel transfer mode
Supports SD 4-bit parallel transfer mode
Supports UHS-104 SD 4-bit card (version 3.0)
Supports CF v6.0 with PIO mode 6 and Ultra DMA 7 mode

Interface Type USB 3.0 High-speed interface
NOTE: If there is a USB2 connection, USB2 transfer speeds are supported.

Dimensions (WxHxD) 4.9 x 4 x 1 in (124.5 x 101.6 x 25.4 mm) Fits conveniently in the 5.25" drive bay.

Supported Media Types CompactFlash Type I
CompactFlash Type II
Microdrive
Secure Digital Card (SD)
Secure Digital High Capacity (SDHC)
SD Extended Capacity Memory Card (SDXC)
SD Ultra High Speed II(SD UHSII)
Memory Stick
Memory Stick Select
Memory Stick Duo (MS Duo)
Memory Stick PRO (MS PRO)
Memory Stick PRO Duo (MS PRO Duo)
Memory Stick PRO-HG Duo
MagicGate Memory Stick (MG)

Technical Specifications - Optical and Removable Storage

MagicGate Memory Stick Duo

These additional media types are supported with a card adapter.

Memory Stick Micro (M2)

miniSD

miniSD High Capacity

Micro SD Memory Card (MicroSD)

Micro SD High Capacity Memory Card (MicroSDHC)

Test Parameters/Conditions - Power applied, unit operating on system
±5%

Operating Systems Supported

Windows 8 Pro (64-bit)*

Windows 8.1 (64-bit)*

Windows 8 (64-bit)*

Windows 7 Professional (32-bit)**

Windows 7 Professional (64-bit)**

Windows Vista Business 64

Windows Vista Business 32

Windows Vista Home Basic 32

Windows XP Professional

Windows XP Home 32

No driver is required for this device. Native support is provided by the operating system.

Not all features are available in all editions of Windows 8. Systems may require upgraded and/or separately purchased hardware, drivers and/or software to take full advantage of Windows 8 functionality. See <http://www.microsoft.com>.

<http://www.microsoft.com>.

Not all features are available in all editions of Windows 7. This system may require upgraded and/or separately purchased hardware to take full advantage of Windows 7 functionality.

See <http://www.microsoft.com/windows/windows-7/> for details.

Kit Contents

Media card reader, 5.25" bracket/rails/bezel, Install Guide, IO & Security Software and Documentation CD

Approvals

USB-IF, WHQL, Compliant with USB Mass Storage Class Bulk only Transport Specification Rev. 1.0,

Compliant Intel Front Panel I/O Connectivity Design Guide V. 1.3, FCC, CE, BSMI, C-Tick, VCCI, MIC, cUL, TUVT

Weight

0.35 lbs. (0.16 kg)

Technical Specifications - Controller Cards

CONTROLLER CARDS

HP IEEE 1394b FireWire PCIe Card	Data Transfer Rate	Supports up to 800 Mb/s	
	Devices Supported	IEEE-1394 compliant devices	
	Bus Type	PCIe card full height PCIe slots	
	Ports	Two IEEE-1394b external 9-Pin connectors (Rear)	
	Internal Connectors	One 10-Pin header connector	
	System Requirements	Windows 8.1 64-bit, Windows 7 Professional 32-bit and 64-bit, SLED 11 and RHEL 6. Intel i5 series or higher processor, min 2GB of RAM, 20GB Hard Drive, CD-ROM drive, built in sound system, Available PCIe slot.	
	Temperature – Operating	50° to 131° F (10° to 55° C)	
	Temperature – Storage	-22° to 140° F (-30° to 60° C)	
	Relative Humidity – Operating	20% to 80%	
	Compliances	FCC Part 15B, cULus 60950, CE Mark EN55022B(1995)/EN55024-1998 STD, Taiwan BSMI CNS13438, Korea MIC	
	Operating Systems Supported	Windows 8.1 64-bit, Windows 7 Professional 32-bit and 64-bit	
	HP Thunderbolt-2 PCIe 1-port I/O Card	Data Transfer Rate	Supports up to 20 Gb/s (20,000 Mb/s)
		Devices Supported	Thunderbolt™ certified devices
Bus Type		PCIe card, full or half height PCIe slots	
Ports		One Thunderbolt™ 2 external 20-Pin output connectors (Rear) One full size DisplayPort input connector (Rear)	
Internal Connectors		One 5-Pin header connector	
System Requirements		Genuine Windows 7 Professional 64-bit, Genuine Windows 8.1 64-bit, Intel i5 series or higher processor, 4-GB RAM, 20-GB Hard Drive, available PCIe slot.	
Temperature - Operating		50° to 131° F (10° to 55° C)	
Temperature - Storage		-22° to 140° F (-30° to 60° C)	
Relative Humidity - Operating		20% to 80%	
Compliances		FCC Part 15B, cULus 60950, CE Mark EN55022B(1995)/EN55024-1998 STD, Taiwan BSMI CNS13438, Korea MIC	
Operating Systems Supported		Genuine Windows 7 Professional 64-bit, Genuine Windows 8.1 64-bit.	
Kit Contents		HP Thunderbolt™ 2 PCIe 1-port I/O Card, full height and half height bracket, DisplayPort to DisplayPort cable, internal header cables (2), user documentation and warranty card.	

Technical Specifications - Networking and Communications

NETWORKING AND COMMUNICATIONS

HP X520 10GbE Dual Port Adapter **Hardware Certifications** FCC B, UL, CE, VCCI, BSMI, CTICK, KCC

HP 10GbE SFP+ SR Transceiver

Operating Temperature 0C to 45C (32F to 113F)

Operating Humidity 0% to 85%, noncondensing

Dimensions (H x W x D) 0.47(h) x 0.54(w) x 2.19(d)inches (1.19 x 1.38 x 5.57 cm)

Intel 7260 802.11 a/b/g/n PCIe WLAN NIC

Operating Humidity Operating 10% to 90% (non-condensing)
Non-operating 5% to 95% (non-condensing)

Dimensions (H x W x D) Native HMC: 26.8 x 30.0 x 2.4 mm
Carrier Card Assembly 3.3 x 4.7 in (84 x 119 mm)

Kit Contents PCIe x1 card with full height bracket, rf antenna, antenna cable, separate low profile bracket, software CD and warranty.

NOTES:

1. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows XP. WLAN may also be compatible with certain third-party software supplicants. WLAN supplier IHV extensions required for Cisco Compatible Extensions support for Microsoft Windows Vista.
2. Check latest software/driver release for updates on supported security features.
3. Maximum output power may vary by country according to local regulations.
4. In Power Save Polling mode and on battery power.
5. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CCK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
6. 802.11a/g (OFDM modulation).

Integrated Intel I210AT PCIe GbE Controller

Connector RJ-45 (motherboard integration)

Controller Intel I210 GbE platform LAN connect networking controller

Memory Programmable FIFO packet buffer memory
Tx 24KB default
Rx up to 16KB

Data Rates Supported 10/100/1000 Mbps

Compliance 802.1as, 802.1q, 802.1Q, 802.3, 802.3ab, 802.3ap, 802.3az, 802.3u, 802.3x, 802.3z

Bus Architecture PCI Express 2.1 (x1) and SMBus

Data Transfer Mode PCIe-based interface for active state operation (S0 state) and SMBus for host and management traffic (Sx low power state)

Power Requirement Requires 3.3V only (integrated regulators)

Boot ROM Support Yes

Network Transfer Mode Full-duplex; Half-duplex (not supported for the 1000BASE-T transceiver)

Network Transfer Rate 10BASE-T (half-duplex) 10 Mbps
10BASE-T (full-duplex) 20 Mbps
100BASE-TX (half-duplex) 100 Mbps
100BASE-TX (full-duplex) 200 Mbps

Technical Specifications - Networking and Communications

		1000BASE-T (full-duplex) 2000 Mbps
	Management Capabilities	WOL, auto MDI crossover, PXE, Multi-port teaming, RSS, Advanced cable diagnostics
Integrated Intel I218LM PCIe GbE Controller	Connector	RJ-45 (motherboard integration)
	Controller	Intel I218LM GbE platform LAN connect networking controller
	Memory	3 KB FIFO packet buffer memory (both Tx and Rx)
	Data Rates Supported	10/100/1000 Mbps
	Compliance	802.1as, 802.1p, 802.1Q, 802.3, 802.3ab, 802.3az, 802.3i, 802.3u, 802.3x, 802.3z
	Bus Architecture	PCI Express 1.1 (x1) and SMBus
	Data Transfer Mode	PCIe-based interface for active state operation (S0 state) and SMBus for host and management traffic (Sx low power state)
	Power Requirement	Requires 3.3V only (integrated regulators)
	Boot ROM Support	Yes
	Network Transfer Mode	Full-duplex; Half-duplex (not supported for the 1000BASE-T transceiver)
	Network Transfer Rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps
	Management Capabilities	WOL, auto MDI crossover, PXE, Multi-port teaming, RSS, Advanced cable diagnostics AMT 9.1 support, vPro compliant
	HP 361T PCIe Dual Port Gigabit NIC	Connector
Controller		Intel® Ethernet I350 Controller
Data Rates Supported		10/100/1000 Mbps, Half- and full-duplex
Compliance		802.3, 802.3u, 802.3x, 802.3ab, 802.3ad, 802.1p, 802.1Q, 802.3az, IEEE 1588 PCIe v2.0 standard RoHS (6 of 6) FCC (U.S. only) Class B DOC (Canada) Class B CE EN 55024, EN55022 Class B VCCI Class II UL 1950 CSA 950 EN 60950 CE ACPI 1.1a Microsoft WHQL (Windows Hardware Quality Labs)
Data Path Width		Four lane (x4) PCI Express compatible with x4, x8, and x16 PCI Express slots
Power Requirement		4.1W idle without EEE link partner 3.2W idle with EEE link partner 4.2W maximum
Network Transfer Rate		10BASE-T (half-duplex) 10 Mb/s 10BASE-T (full-duplex) 20 Mb/s 100BASE-TX (half-duplex) 100 Mb/s

Technical Specifications - Networking and Communications

100BASE-TX (full-duplex) 200 Mb/s
1000BASE-T (full-duplex) 2000 Mb/s

Operating Temperature	32° to 131° F (0° to 55° C)
Operating Humidity	10% to 95% non-condensing
Dimensions (H x W x D)	5.3 x 2.5 in (13.50cm x 6.4 cm) (without brackets)
Operating System Driver Support	Windows 7 Professional 32-bit and 64-bit. Red Hat Enterprise Linux(RHEL) WS4, 5, 6 Desktop/Workstation Novell SLED 10 & SLED 11
Kit Contents	HP 361T PCIe Dual Port Gigabit NIC PCA with a standard height bracket attached to it (the low profile bracket is included in the clamshell that the PCA ships in) Product Warranty statement and the Quick Install Card (QIC).

Intel X540-T2 10GbE Dual Port Adapter **Operating Temperature** 32° to 131° F (0° to 55° C)

Operating Humidity	5% to 95% non-condensing
Dimensions (H x W x D)	Standard PCIe with full height bracket installed, half height bracket included. 0.7 x 2.7 x 6.0 in
Operating System Driver Support	The HP driver drop is a unified package that includes the X540-T2 driver. It is the same driver as is used for the 561T. Currently, it includes drivers for Win7-32, Win7-x64, Win8-x64, and Win81-x64.
Kit Contents	Intel X540 10Gb Ethernet Dual port adapter, Installation guide, Warranty card. Windows Server 2012 R2, Windows Server 2012, Windows 8, Windows Server 2008 R2, Windows 7, Windows Server 2008 SP2, Windows Vista SP2, Windows Server 2003 R2, Windows Server 2003 SP2, Linux Stable Kernel version 3.x, 2.6,x, Red Hat Enterprise Linux 5, 6, SUSE Linux Enterprise Server 10, 11, FreeBSD 9, VMware ESX/ESXi. Note: Not all OS's supported on all HP Z Workstations.

Summary of Changes

SUMMARY OF CHANGES

Date of change:	Version History:		Description of change:
August 21, 2014	v1	Added	Style and technical specifications
October 24, 2014	From v1 to v2	Added	note to supported components: memory, Foxit PhantomPDF Express and Cyberlink Power2Go: software, Optical drives: DVD, BD-XL specs
November 1, 2014	From v2 to v3	Added	Note for Internal USB connector conversion, Overview,
		Changed	Internal USB statement in Overview and System Board sections
December 1, 2014	From v3 to v4	Added	Intel X540-T2 10GbE Dual Port Adapter, HP 4-in-1 SFF (2.5in) HDD Carrier
January 1, 2015	From v4 to v5	Added	RHEL for Preinstalled OS, AMD FirePro W7100, Tesla K40 to GPU and High Performance Computing; Ubuntu 14.04 for Supported Components
		Changed	Memory Load Order, High Performance Computing for K40
February 1, 2015	From v5 to v6	Added	Windows 8.1 Pro 64-bit OS, Red Hat Enterprise Linux (RHEL), HP DX115 Removable HDD Carrier, and notes, 4-Bay SAS-SATA and notes, HP 4-Bay SAS-SATA 2.5in High Density Storage Kit
		Changed	Overview OS, Processors table Power Supply table, Hard Drives Notes, Optical and Removable Storage order, Power Consumption and Chassis Fan
		Removed	Windows 7 Professional 64-bit (National Academic)
March 1, 2015	From v6 to v7	Added	Overview: RAID support. Supported Components, Hard Drives: New SAS SFF 15 HDD line and notes, 4TB SATA HDD
		Changed	SAS, and SATAHDD Description Notes. System Board: Memory section.
April 1, 2015	From v7 to v8	Added	NVIDIA Quadro M6000 12GB Graphics, Memory notes
		Changed	Memory from Supported Components, Memory Speed Supported from System Board, ACPI version updated in BIOS section.

© 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Xeon, and Thunderbolt are trademarks of Intel Corporation in the U.S. and other countries. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation. Red Hat is a registered trademark of Red Hat, Inc. in the United States and other countries. Firewire is a trademark of Apple Inc. Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.